

EUROLITE DPMX-1216 S DMX Dimmer Pack

12 x 16A dimmer, service friendly modules, 12 safety sockets

Art. No.: 70064182

GTIN: 4026397521764



Description:

Reliability is always important. Especially at professional events the breakdown of any part of the equipment cannot be accepted. The DPMX-1216 dimmer pack series is the right answer here because it plays it safe: this universal output stage has an automatic circuit breaker on every channel, so single failures can be corrected without causing a complete blackout. Another benefit are the different outputs. Pole connector, safety plug, CEE or multipin: the DPMX-1216 19" serves really any kind.

Logistic

EAN / GTIN: 4026397521764

Weight: 20,45 kg

Length: 0.61 m

Width: 0.56 m

Height: 0.30 m

Features:

- 12-channel dimmer pack with up to 16 A output per channel
- Modular design of the individual dimmer modules for quick and easy change
- 3-phase or 1-phase power supply
- Adjustable lamp preheat (0-50%) and limiter function to prolong bulb life
- Curve function for selection of different fade modes
- Dim or switch option assignable to each channel
- DMX Fail function: automatic digital input check to detect DMX signal errors
- Manual mode for dimming capability without an external lighting controller
- Synchronization of several devices possible via DMX
- Automatic circuit breaker per channel (type C)
- Channel outputs on the rear panel via safety sockets
- Only for professional use
- 12 integrated show programs
- Preprogrammed 12 scenes/chases
- Control via stand-alone; DMX
- (19") 48.3 cm rack installation 4 U
- For application areas such as: Trade fair and shop fitting; stage; theater; rental

- Very quiet working noise

Technical specifications:

| | |
|--------------------------------|--|
| Power supply: | 230/380 V AC, 50 Hz |
| Output power: | Max. 43470 W Max. 3680 W per channel |
| Output current: | Max. 189 A |
| Power connection: | Mains input via screw terminal |
| Power output: | 12 x safety contact (F), hinged lid mounting version |
| Power output fuse per channel: | C 16 A fuse resettable |
| Programs: | Preprogrammed 12 scenes/chases |
| DMX channels: | 12 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Control: | Stand-alone; DMX |
| Control channels: | 12 |
| Color: | Black |
| Housing design: | (19") 48.3 cm rack installation 4 U |
| Dimensions: | Width: 48.3 cm Depth: 52.0 cm Height: 17.8 cm |
| Weight: | 17.70 kg |
| Noise classification: | Class 1 (very slight noise, suitable for noise-sensitive environments) |

Scope of delivery:

- 1 x device
- 1 x user manual