EUROLITE QuickDMX Outdoor Wireless Transmitter/Receiver

Weather-proof wireless DMX transceiver, IP65

Art. No.: 70064710

GTIN: 4026397702408

List price: 224.91 €

incl. 19% VAT.

Features:

- Auto-switching transceiver
- Adaptive frequency hopping ensures interference-free operation in the 2.4 GHz band
- Multicolored LED indicator
- Lockable power input (IP T-Con)
- Control via QuickDMX; plug and play
- Operating range up to 600m with line-of-sight
- Up to 6 transmitters can be operated in parallel without interference
- With Omega bracket
- Suitable for outdoor use IP65

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x declaration of conformity, 1 x omega bracket

Logistic

EAN / GTIN: 4026397702408
Weight: 1,55 kg
Length: 0.30 m
Width: 0.20 m
Heigth: 0.14 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP65
Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug (provided)
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Control:	QuickDMX; plug and play
Range:	Range up to 600m with line-of-sight

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Carrier frequency:	2,4 GHz
Parallel mode:	Max. 6 transmitter
Modulation:	GFSK
Attachment system:	Omega bracket
Color:	Black
Dimensions:	Length: 17,3 cm Width: 15,6 cm Height: 9,2 cm
Weight:	1,28 kg

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.