

EUROLITE DMX Power Splitter 4x4 3-pin XLR

1 in/4 out power and DMX splitter with RDM support for rack mounting

Art. No.: 70064806

GTIN: 4026397688702



List price: 189.21 €

incl. 19% VAT.

Description:

The 4-fold splitter is designed for reliable distribution of DMX512 signals and operation voltage (max. 16 A). The unit features one DMX input and four DMX outputs with status indicators as well as a feed-through terminal for connection to an additional splitter. The mains connectors are designed as P-Con sockets. The splitter supports RDM for bidirectional communication over the DMX line and is suitable for mounting in an equipment rack.

Logistic

EAN / GTIN: 4026397688702

Weight: 2,75 kg

Length: 0.52 m

Width: 0.23 m

Height: 0.10 m

Features:

- 1 P-Con input to 4 outputs, max. 16 A
- 1 DMX input to 4 outputs
- 1 DMX feed-through output
- Switchable RDM filter mode
- Switchable termination resistor
- Input and outputs galvanically isolated
- (19") 48.3 cm rack installation 1 U
- Each DMX output with independent driver and status indicator
- Control via DMX; RDM

Package contents

- 1 x device, 1 x user manual, 1 x power cord

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 5 W

Protection class:	Protection class I
Output current:	Max. 4 x 4 A per channel
Power connection:	Via P-Con (blue), mounting version
Power output:	4 x P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 1 A fuse replaceable
DMX input:	1 x 3-pin XLR (M)
DMX output:	4 x 3-pin XLR (F) with independent driver and status indicator
Control:	DMX; RDM
Housing color:	Black
Housing design:	(19") 48.3 cm rack installation 1 U
Dimensions:	Width: 48,3 cm Depth: 13,8 cm Height: 4,3 cm
Weight:	2,38 kg