

## EUROLITE LSD-75E MK2 custom / per m<sup>2</sup>

Custom sizes for LED soft displays (economy version)

Art. No.: 80503233

GTIN: 4026397542578



**The article is no longer in our assortment.**

### Features:

- Fully assembled LED soft displays (economy version) produced according to your individual dimensions - contact our sales team!
- Production of model LSD-100E available in steps of 1.2 meters (equals 16 pixels)
- Maximum size 1280 x 1024 pixels
- For quick 2-man installation and uncomplicated transport, a size of up to 5 meters per display is recommended
- Price per square meter
- Available in black and white
- Regular delivery time by sea freight: about 9 weeks
- Short-term delivery by air freight: about 4 weeks

### Logistic

EAN / GTIN: 4026397542578

Weight: 5,45 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

### Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	4,00 W
IP classification:	IP44
Dimensions:	Width: 1,2 m Height: 2,4 m
Weight:	5,45 kg
Resolution (W x H):	16 x 32 pixels
Pixel pitch:	75 mm

Pixel density:	177/m <sup>2</sup>
Pixel configuration:	tri-color RGB LEDs, type SMD 3528
Lifetime:	approx. 100000 hours
Display port:	DVI/RJ45
Display mode:	synchronous to video source
Drive mode:	1/8 scan
Screen resolution:	max. 1280 x 1024 (LED Studio) max. 1024 x 896 (LED Show T9)
Brightness:	75 cd/m <sup>2</sup> (nits)
Viewing angle:	120°
Frame rate:	60 Hz
Data refresh rate:	600 Hz
Colors:	16.7 million (R 256, G 256, B 256)
Protection grade:	IP44
Operating temperature:	-10 to 45 °C
Humidity:	10 to 90 %
Dimensions (W x H):	1200 x 2400 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting