

EUROLITE LSD-50E MK2 custom / per m²

Custom sizes for LED soft displays (economy version)

Art. No.: 80503235

GTIN: 4026397542585



The article is no longer in our assortment.

Features:

- Fully assembled LED soft displays (economy version) produced according to your individual dimensions - contact our sales team!
- Production of model LSD-50E available in steps of 0.8 meters (equals 16 pixels)
- Maximum size 1280 x 1024 pixels
- For quick 2-man installation and uncomplicated transport, a size of up to 5 meters per display is recommended
- Price per square meter
- Available in black and white
- Regular delivery time by sea freight: about 9 weeks
- Short-term delivery by air freight: about 4 weeks

Logistic

EAN / GTIN: 4026397542585

Weight: 7,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Technical specifications:

| | |
|---------------------|-------------------------------|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 10,00 W |
| IP classification: | IP44 |
| Dimensions: | Width: 1,6 m Height: 2,4 m |
| Weight: | 7,00 kg |
| Resolution (W x H): | 32 x 48 pixels |
| Pixel pitch: | 50 mm |

| | |
|------------------------|--|
| Pixel density: | 400/m ² |
| Pixel configuration: | tri-color RGB LEDs, type SMD 3528 |
| Lifetime: | approx. 100000 hours |
| Display port: | DVI/RJ45 |
| Display mode: | synchronous to video source |
| Drive mode: | 1/8 scan |
| Screen resolution: | max. 1280 x 1024 (LED Studio) max. 1024 x 896 (LED Show T9) |
| Brightness: | 150 cd/m ² (nits) |
| Viewing angle: | 120° |
| Frame rate: | 60 Hz |
| Data refresh rate: | 600 Hz |
| Colors: | 16.7 million (R 256, G 256, B 256) |
| Protection grade: | IP44 |
| Operating temperature: | -10 to 45 °C |
| Humidity: | 10 to 90 % |
| Dimensions (W x H): | 1600 x 2400 mm |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |