


EUROLITE PSS-4/75 Pixel String

Flexible LED pixel string

Art. No.: 80503360

GTIN: 4026397423488



The article is no longer in our assortment.

Features:

- Flexible pixel string with ultra-bright TCL LEDs
- 32 pixels with 4 LEDs each
- Bright and colorful projection of videos and graphics
- Can be arranged into virtually any form even on uncommon surfaces for creative freedom
- Modular concept allows build-up of large video displays for clubs, stages, shops and various other environments - also for billboards on buildings
- Can be extended up to 40 meters with 340 pixels
- IP65 for indoor and outdoor use
- Pixels individually controllable
- Independent control of color, effects and animations
- Control per network protocol with PC software or PSS media player (accessories)
- Control also possible per MADRIX, DMX and Artnet
- Large operating range from -20° to +50° C

Logistic

EAN / GTIN: 4026397423488

Weight: 0,46 kg

Length: 0.30 m

Width: 0.20 m

Height: 0.08 m

Technical specifications:

Power consumption: 260,00 W

IP classification: IP65

Dimensions: Width: 2,3 cm
Depth: 1 cm
Height: 3,8 cm

Weight: 400 g

Pixel pitch:	75 mm
Pixel configuration:	4 RGB LEDs (TCL)
Pixels per string:	32
Pixel size (W x D x H):	23 x 38 x 10 mm
String length:	3 m
Max. string length:	40 m
Total max. pixels:	340
Brightness:	2.5 cd per pixel
Bit depth per color:	16
Bit depth per pixel:	48
Viewing angle:	120° x 120°
Lifetime:	approx. 80000 hours
Control protocol:	TCP/IP
Control system:	PSS-4
Display mode:	synchronous to video source
Protection grade:	IP65
Material:	clear polycarbonate
	black cable
Operating temperature:	-20 to 50 °C
Power supply:	15 V DC via control system PSS-1
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting