

OMNITRONIC MP-120P PA mixing Amplifier

PA mixing amplifier with audio player, IR remote control, 120 W RMS

Art. No.: 80709621 GTIN: 4026397503456







List price: 403.41 €

incl. 19% VAT.

Features:

- SD card slot and USB port

- Folder navigation and repeat functions (1, All)
- 3 microphone inputs (6.3 mm jack, unbal.) with separate level controls
- Microphone input 3 with adjustable priority circuit
- 3 line inputs (stereo RCA) with separate level controls
- 1 line output (stereo RCA)
- Chime, switchable
- Treble and bass control for the output signal
- 7-digit LED level meter
- Master control for the output signal
- (19") 48.3 cm rack installation 2 U
- The device is cooled by cooling fan
- Control via IR remote control

- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms Package contents

- 1 x amplifier, 1 x user manual, 1 x remote control, 1 x battery

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	240,00 W
Protection class:	Protection class I
Output power:	120 W RMS

Logistic

EAN / GTIN: 4026397503456 Weight: 10,65 kg Length: 0.54 m Width: 0.49 m Heigth: 0.18 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection:	Fixed power supply cord with safety plug
Device fuse:	5 x 20 mm, T 2 A fuse replaceable
Frequency range:	80 - 14000 Hz
S/N ratio:	>75 dB microphone >85 dB line
THD:	<0,5 % at 1 kHz
Cooling:	Cooling fan
Impedance:	Public address systems 100V; 4-16 ohms; Public address systems 70V
Control:	IR remote control
Audio player:	USB + SD
Housing color:	Black
Circuitry:	Class AB
Controls:	Power on/off transient; Overvoltage; short-circuit
Connections:	Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version)
	Input: line via 3 x stereo RCA 0,3 V
	Output: line via 1 x stereo RCA 0,3 V
	Output: speaker via screw terminal
Equalizer:	Master: 1 x 2-band tone control mono
Music format:	MP3
Number of files:	Max. 999
Available storage media:	USB devices/SD cards max. 32GB (FAT 32)
Housing design:	(19") 48.3 cm rack installation 2 U
Dimensions:	Width: 48,3 cm
	Depth: 40 cm
	Height: 8,9 cm
Weight:	9,00 kg
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in