

OMNITRONIC MP-350P PA Mixing Amplifier

PA mixing amplifier with audio player, IR remote control, 350 W RMS

Art. No.: 80709645

GTIN: 4026397504019



Features:

- SD card slot and USB port
 - Folder navigation and repeat functions (1, All)
 - 3 microphone inputs (6.3 mm jack, unbal.) with separate level controls
 - Microphone input 3 with adjustable priority circuit
 - 3 line inputs (stereo RCA) with separate level controls
 - 1 line output (stereo RCA)
 - Chime, switchable
 - Treble and bass control for the output signal
 - 7-digit LED level meter
 - Master control for the output signal
 - (19") 48.3 cm rack installation 2 U
 - Highly efficient air flow from front to rear
 - The device is cooled by temperature-controlled fan
 - For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms
- audio player**
- Control via IR remote control
 - LCD display

Logistic

EAN / GTIN: 4026397504019

Weight: 14,15 kg

Length: 0.54 m

Width: 0.49 m

Height: 0.18 m

Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 700.00 W

Protection class: Protection class I

| | |
|--------------------------|---|
| Output power: | 350 W RMS |
| Power connection: | Fixed power supply cord with safety plug |
| Device fuse: | 5 x 20 mm, T 5 A fuse replaceable |
| Frequency range: | 80 - 14000 Hz |
| S/N ratio: | >75 dB microphone >85 dB line |
| THD: | <0.5 % at 1 kHz |
| Cooling: | Temperature-controlled fan , air flow from front to rear |
| Impedance: | 4-16 ohms; public address systems 100V; Public address systems 70V |
| Circuitry: | Class AB |
| Control elements: | Power switch, Master control, tone control, regular talkover |
| Controls: | Power on/off transient; Overvoltage; short-circuit |
| Status LED: | Power, fault, master level meter |
| Connections: | Input: microphone via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: line via 3 x stereo RCA 0.3 V Output: rec. via 1 x stereo RCA 0.3 V Output: speaker via screw terminal |
| Channels: | Microphone channel: 1 x mono via Combination socket (XLR/jack), channel control via rotary dial Microphone channel: 2 x mono via jack, channel control via rotary dial Input channel: 3 x stereo via RCA, channel control via rotary dial Input channel: via audio player, channel control via rotary dial, mute control Master output: mono, channel control via rotary dial, 2-band tone control EQ |
| Material: | Metal |
| Color: | Black |
| Housing design: | (19") 48.3 cm rack installation 2 U |
| Dimensions: | Width: 48.3 cm Depth: 40 cm Height: 8.9 cm |
| Weight: | 12.45 kg |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Control: | IR remote control |
| Audio player: | USB + SD |
| Display type: | LCD display |
| Music format: | MP3, WMA; FLAC, WAV |
| Number of files: | Max. 999 |
| Available storage media: | USB devices/SD cards max. 32GB (FAT 32) |

Scope of delivery:

- 1 x amplifier
- 1 x remote control
- 1 x user manual
- 1 x battery