

## **OMNITRONIC MPVZ-250.6 PA Mixing Amplifier**

6 zone PA mixing amplifier adjustable zones, 250 W RMS

Art. No.: 80709786 GTIN: 4026397422177









**List price: 612.85 €** 

incl. 19% VAT.

## Features:

- Comfortable control of PA speakers via 6-zone technology
- 6 PA zone outputs with separate 5-step level controls
- Output for low-impedance speakers (4-16 ohms)
- 2 rear microphone inputs (6.3 mm jack, unbal.)
- 1 front microphone input (combination XLR/6.3 mm jack, unbal.) with adjustable priority circuit
- All microphone inputs with separate level controls
- 3 line inputs (stereo RCA) with separate level controls
- 1 line output (stereo RCA)
- Chime, switchable
- Treble and bass control for the output signal
- 7-digit LED level meter
- Master control for the output signal
- The device is cooled by cooling fan
- (19") 48.3 cm rack installation 2 U
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms
  Package contents
- 1 x amplifier, 1 x user manual

## **Technical specifications:**

Power supply:	230 V AC, 50 Hz
Power consumption:	500,00 W
Output power:	250 W RMS

## Logistic

EAN / GTIN: 4026397422177

Weight: 12,75 kg Length: 0.56 m Width: 0.47 m Heigth: 0.18 m

Output current:	Max. 2,5 A
Power connection:	Fixed power supply cord with safety plug
Frequency range:	80 - 16000 Hz
S/N ratio:	>75 dB Microphone >85 dB line
THD:	<0,5 % at 1 kHz
Cooling:	Cooling fan
Impedance:	4 ohms; 8 ohms; 16 ohms; Public address systems 100V; Public address systems 70V
Zone output:	6 adjustable zones
Circuitry:	Class AB
Controls:	Current limiting; short-circuit; power on/off transient; power on/off transient; Overvoltage; short-circuit
Status LED:	Power, fault, level meter
Connections:	Input: Microphone via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version)
	Input: Microphone via 2 x 6.3 mm plug (unbal.)
	Input: line via 3 x stereo RCA 0,3 V
	Output: line via 1 x stereo RCA
	Output: speaker via screw terminal
Equalizer:	Master: 1 x 2-band tone control mono
Housing design:	(19") 48.3 cm rack installation 2 U
Dimensions:	Width: 48,3 cm
	Depth: 38,5 cm
	Height: 8,9 cm
Weight:	11,15 kg