

OMNITRONIC MPVZ-350.6 PA Mixing Amplifier

6 zone PA mixing amplifier adjustable zones, 350 W RMS

Art. No.: 80709791

GTIN: 4026397422184



Features:

- Comfortable control of PA speakers via 6-zone technology
- 6 PA zone outputs with separate 5-step level controls
- Output for low-impedance speakers (4-16 ohms)
- 2 rear microphone inputs (6.3 mm jack, unbal.)
- 1 front microphone input (combination XLR/6.3 mm jack, unbal.) with adjustable priority circuit
- All microphone inputs with separate level controls
- 3 line inputs (stereo RCA) with separate level controls
- 1 line output (stereo RCA)
- Chime, switchable
- Treble and bass control for the output signal
- 7-digit LED level meter
- Master control for the output signal
- (19") 48.3 cm rack installation 2 U
- Highly efficient air flow from front to rear
- The device is cooled by temperature-controlled fan
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms

Logistic

EAN / GTIN: 4026397422184

Weight: 14,30 kg

Length: 0.53 m

Width: 0.49 m

Height: 0.18 m

Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 700.00 W

Output power: 350 W RMS

Power connection: Fixed power supply cord with safety plug

| | |
|-------------------|--|
| Frequency range: | 80 - 16000 Hz |
| S/N ratio: | >75 dB microphone >85 dB line |
| THD: | <0.5 % at 1 kHz |
| Cooling: | 1 x temperature-controlled fan , air flow from front to rear |
| Impedance: | Public address systems 100V; 4-16 ohms; Public address systems 70V |
| Zone output: | 6 adjustable zones |
| Circuitry: | Class AB |
| Control elements: | Power switch |
| Controls: | Current limiting; short-circuit; power on/off transient; power on/off transient; Overvoltage; short-circuit |
| Status LED: | Power, fault, level meter |
| Connections: | Input: microphone via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: line via 3 x stereo RCA 0.3 V Output: rec. via 1 x stereo RCA Output: speaker via screw terminal |
| Equalizer: | Master: 1 x 2-band tone control mono |
| Material: | Metal |
| Color: | Black |
| Housing design: | (19") 48.3 cm rack installation 2 U |
| Dimensions: | Width: 48.3 cm Depth: 38.5 cm Height: 8.9 cm |
| Weight: | 12.80 kg |

Scope of delivery:

1 x amplifier
1 x user manual