

OMNITRONIC PAP-60 PA Amplifier

PA power amplifier, 60 W RMS

Art. No.: 80709804

GTIN: 4026397582055



The article is no longer in our assortment.

Description:

Reliable amplifier

The Omnitronic PAP-60 ELA mixer amplifier is your reliable partner for ELA sound reinforcement systems. Thanks to its 19" format, it is ideal for both mobile and fixed installations.

Outputs for ELA loudspeakers with 70 V and 100 V audio carriers or 4-16- ? loudspeakers leave nothing to be desired. In addition to a line input, the PAP-60 also offers a loop-through output. Choose between XLR and 6.3 mm jack for both. So you're always flexible.

Protection

A fan protects the interior of your PAP-60 from overheating. In addition to a switch-on delay, it also features protection circuits against overload, short-circuit and DC voltage. In these cases, your loudspeakers are electrically isolated from the amplifier. Both the PAP-60 and your speakers are protected from damage.

Features:

- 1 line input (optionally XLR or 6.3 mm jack)
- 1 feed-through output (optionally XLR or 6.3 mm jack)
- 70 V, 100 V or 4-16 ohms operation
- Master control
- LED indicators for power, signal, clip and fault
- Protective circuits: over load, short circuit, turn-on delay, over heating, DC offset protection
- Load detection and power control
- Rack installation
- (19") 48.3 cm rack installation 2 U

Logistic

EAN / GTIN: 4026397582055

Weight: 9,60 kg

Length: 0.54 m

Width: 0.47 m

Height: 0.18 m

Package contents

- 1 x user manual, 1 x amplifier

Technical specifications:

| | |
|-------------------|--|
| Power supply: | 230 V AC, 50 Hz |
| Output power: | 60 W RMS |
| Power connection: | Fixed power supply cord with safety plug |
| Frequency range: | 60 - 16000 Hz |
| S/N ratio: | >90 dB line |
| THD: | <0,5 % at 1 kHz |
| Impedance: | Public address systems 100V; 4-16 ohms |
| Circuitry: | Class AB |
| Controls: | Softstart; overheat; overload; short-circuit; DC voltage |
| Status LED: | Signal, power, fault, clip |
| Connections: | Input: line via 1 x 6.3 mm jack socket (mono) mounting version Input: line via 1 x 3-pin XLR 0,8 V Output: line via 1 x 6.3 mm jack socket (mono) mounting version Output: line via 1 x 3-pin XLR |
| Housing design: | (19") 48.3 cm rack installation 2 U |
| Dimensions: | Width: 48,3 cm Depth: 38,5 cm Height: 8,9 cm |
| Weight: | 7,90 kg |