

OMNITRONIC PAP-120 PA Amplifier

PA power amplifier, 120 W RMS

Art. No.: 80709806

GTIN: 4026397582062



List price: 320.11 €

incl. 19% VAT.

Features:

- 1 line input (optionally XLR or 6.3 mm jack)
- 1 feed-through output (optionally XLR or 6.3 mm jack)
- Master control
- LED indicators for power, level, clip and fault
- Load detection and power control
- (19") 48.3 cm rack installation 2 U
- Highly efficient air flow from front to rear
- The device is cooled by temperature-controlled fan
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms

Package contents

- 1 x amplifier, 1 x user manual

Logistic

EAN / GTIN: 4026397582062

Weight: 9,80 kg

Length: 0.54 m

Width: 0.47 m

Height: 0.18 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Protection class:	Protection class I
Output power:	120 W RMS
Power connection:	Fixed power supply cord with safety plug
Frequency range:	60 - 16000 Hz
S/N ratio:	>90 dB
THD:	<0,5 % at 1 kHz

Cooling:	Temperature-controlled fan , air flow from front to rear
Impedance:	4-16 ohms speaker; public address systems 100V speaker; Public address systems 70V
Circuitry:	Class AB
Control elements:	Level control, power switch
Controls:	Softstart; overheat; overload; short-circuit; DC voltage
Status LED:	Power, signal, fault, clip
Connections:	Input: line via 1 x 6.3 mm jack socket (mono) mounting version Input: line via 1 x 3-pin XLR (F) mounting version 0,8 V Output: line via 1 x 6.3 mm jack socket (mono) mounting version Output: line via 1 x 3-pin XLR (M) mounting version Output: speaker via screw terminal
Material:	Metal
Color:	Black
Housing design:	(19") 48.3 cm rack installation 2 U
Dimensions:	Width: 48,3 cm Depth: 38,5 cm Height: 8,9 cm
Weight:	8,15 kg