

OMNITRONIC EIO3-50III PA mixing amplifier

PA mixing amplifier with CD receiver with SD slot, USB and AUX input

Art. No.: 80709870

GTIN: 4026397396669



The article is no longer in our assortment.

Features:

- FM/AM tuner with 24 memory places and station finding
- CD/MP3 player for CD-DAs, CD-Rs, CD-RWs
- USB2.0 input
- SD(HC) card slot
- Front aux input
- Plays WAV, WMA, MP3 (CBR and VBR files)
- Blue backlit LCD with ID3 tag indication (song, artist, album)
- Loudness function
- Folder navigation
- +10 and -10 button
- Repeat functions, random play, scan
- Amplifier output power: 1 x 50 W RMS
- 3 microphone inputs (6.3 mm jack) with separate level controls
- Input 1 with priority circuit
- Input 3 switchable to line level
- Siren, switchable
- 2-way tone control (treble, bass)
- 5-fold LED level display
- PA speaker outputs (25V, 50V, 70V, 100V) via terminal blocks
- 4-ohm output for passive speaker
- Protection circuits: over current, short circuit, turn-on delay
- Mains operation or 12 V battery operation
- Brackets for rack installation

Logistic

EAN / GTIN: 4026397396669

Weight: 9,35 kg

Length: 0.54 m

Width: 0.39 m

Height: 0.18 m

Technical specifications:

Power consumption:	150,00 W
Output power:	Max. 50 W
Frequency range:	80 - 15000 Hz
Dimensions:	Width: 48,3 cm Depth: 32 cm Height: 8,9 cm
Weight:	8,55 kg
Power supply:	115/230 V AC, 50/60 Hz or 12 V emergency power battery
Output power:	50 W RMS
Output type:	25 V, 50 V, 70 V, 100 V or 4 ohms
Outputs:	screw connectors
Inputs:	2 x mic -50 dB, 600 ohms (6.3 mm jack, unbal.) 1 x aux/mic -20 dB, 10 kohms/-50 dB, 600 ohms (6.3 mm jack, unbal.)
S/N ratio:	105 dB
Distortion:	<0.6 %
Slew rate:	70 V/ms
Tuner channel:	FM 87-108 Hz AM 522-1,161 Hz
Tuner step pace:	FM 50 kHz AM 9 kHz
Available disc:	CD/-R/-RW (12 cm)
USB port (type A):	2.0, downward compatible
Available memory cards:	SD und SDHC
Aux input:	3.5 mm stereo jack
Playback format:	WAV, WMA, MP3
Dimensions:	483 x 320 x 100 mm