

## HONEYWELL Ceiling Speaker L-VCM6A/EN (EN54)

Recessed ceiling speaker with fire dome

Art. No.: 80710009

GTIN: 4026397519044



**The article is no longer in our assortment.**

### Features:

- 2-way coaxial system with 16.5 cm woofer (6.5")
- Fire dome for safety in case of fire
- Sturdy steel grille, white RAL9003
- Easy and super quick installation via clamp system
- For speech and background music in indoor PA systems
- EASE data available in the download section
- Complies with EN 54-24 and EN 60849

### Logistic

EAN / GTIN: 4026397519044

Weight: 1,75 kg

Length: 0.27 m

Width: 0.27 m

Height: 0.17 m

### Technical specifications:

Power connection:	Fixed Supply cord with open wires
Power:	Program: 12W Rated: 6W RMS
Frequency range:	170 - 22000 Hz
Max. SPL:	91 dB
Impedance:	Public address systems 100V
Standard:	EN 54-24, EN 60849
Power tapping:	0,75W; 1,5W; 3W; 6W RMS via no connector/cable only switchable
Speaker:	1 x woofer 6,5"
Type of speaker:	Flush-mount speaker

Mounting dimensions:	Ø 19,5 cm
Dimensions:	Depth: 12,9 cm Diameter: Ø 22,2 cm
Weight:	1,50 kg