

## OMNITRONIC CST-508 2-Way Ceiling Speaker

2-way flush-mount coaxial speaker, LF: 5,3" HF: 0,75", 8 ohms, 30 W RMS, 9,5 cmØ 17,2 cm

Art. No.: 80710214

GTIN: 4026397709094



**List price: 95.08 €**

incl. 19% VAT.

### Description:

The models of the CST series are frameless in-ceiling speakers with a particularly discreet appearance for installation in hotels, restaurants, bars, foyers, training and conference rooms or shopping centers. The 2-way coaxial systems have a frequency response of up to 20 kHz, balanced sound and excellent speech intelligibility. The tweeter is protected against overload by a PTC and can be tilted 30 degrees to adapt to local conditions, as well as freely rotated by 360°. Secure mounting clamps allow for fast and easy attachment. The front grille is exchangeable.

### Logistic

EAN / GTIN: 4026397709094

Weight: 1,66 kg

Length: 0.24 m

Width: 0.24 m

Height: 0.15 m

### Features:

- Excellent sound playback
- With passive 2-way crossover, PTC tweeter protection
- Swivel tweeter
- Level matching switch -3 dB/0 dB/+3 dB
- For speech and background music in indoor PA systems
- Scratchproof and shockproof
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms

#### Package contents

- 1 x speaker, 1 x user manual

### Technical specifications:

Power: Program: 60W  
Rated: 30W RMS

|                      |                                       |
|----------------------|---------------------------------------|
| Frequency range:     | 50 - 20000 Hz                         |
| Sensitivity:         | 86 dB (1W/1m)                         |
| Max. SPL:            | 104 dB                                |
| Dispersion angle:    | 165° Omnidirectional                  |
| Impedance:           | 8 ohms                                |
| Speaker:             | 1 x woofer 5,3"<br>Tweeter 0,75"      |
| Type of speaker:     | Flush-mount speaker                   |
| Material:            | ABS Acrylonitrile butadiene styrene   |
| Color:               | White, scratchproof and shockproof    |
| Mounting dimensions: | 9,5 cm Ø 17,2 cm                      |
| Dimensions:          | Height: 9,6 cm<br>Diameter: Ø 21,1 cm |
| Weight:              | 1,24 kg                               |