

OMNITRONIC CST-808 2-way Ceiling Speaker

🗩 OMNITRONIC

2-way flush-mount coaxial speaker, LF: 8" HF: 1", 8 ohms, 50 W RMS, 14,5 cm x Ø 24,6 cm

The models of the CST series are frameless in-ceiling speakers with a particularly discreet appearance for installation in hotels, restaurants, bars, foyers, training and conference rooms or shopping centers. The 2-way coaxial systems have a frequency response of up to 20 kHz, balanced sound and excellent speech intelligibility. The tweeter is protected against overload by a PTC and can be tilted 30 degrees to adapt to local conditions, as well as freely rotated by 360°. Secure mounting clamps allow for fast and easy attachment. The front grille is exchangeable.

Features:

Description:

- Excellent sound playback
- With passive 2-way crossover, PTC tweeter protection
- Swivel tweeter
- Level matching switch -3 dB/0 dB/+3 dB
- For speech and background music in indoor PA systems
- Scratchproof and shockproof
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms Package contents
- 1 x speaker, 1 x user manual

Technical specifications:

Power:

Program: 100W Rated: 50W RMS

Logistic

EAN / GTIN: 4026397709070 Weight: 3,14 kg Length: 0.32 m Width: 0.32 m Heigth: 0.17 m

List price: 141.61 € incl. 19% VAT.















Art. No.: 80710234 GTIN: 4026397709070

Frequency range:	40 - 20000 Hz
Sensitivity:	88 dB
Max. SPL:	108 dB
Dispersion angle:	100° omnidirectional
Impedance:	8 ohms
Speaker:	1 x woofer 8" Tweeter 1"
Type of speaker:	Flush-mount speaker
Material:	ABS Acrylonitrile butadiene styrene
Color:	White, scratchproof and shockproof
Mounting dimensions:	14,5 cm x Ø 24,6 cm
Dimensions:	Depth: 14,2 cm Diameter: Ø 28,5 cm
Weight:	2,50 kg