

## OMNITRONIC PS-05 Projector Speaker

Bidirectional speaker (2 x 5") with mount, 100 V 5/10W RMS

Art. No.: 80710362

GTIN: 4026397292374



**The article is no longer in our assortment.**

### Features:

- 100 V speaker system for wall and ceiling installation
- 2 built-in speakers for bidirectional radiation
- Connection cable with 3 power taps
- Weather-proof (IP44), scratch-resistant aluminum housing
- For outdoor and indoor amplifying systems
- Suitable for outdoor use IP44
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Logistic

EAN / GTIN: 4026397292374

Weight: 3,00 kg

Length: 0.17 m

Width: 0.18 m

Height: 0.25 m

### Technical specifications:

|                    |   |
|--------------------|---|
| IP classification: | IP44  |
| Power:             | Program: 20W<br>Rated: 10W RMS                              |
| Frequency range:   | 130 - 15000 Hz  |
| Sensitivity:       | 91 dB   |
| Max. SPL:          | 97 dB   |
| Impedance:         | Public address systems 100V                                 |
| Power tapping:     | 2,5W; 5W; 10W RMS via no connector/cable only<br>switchable |
| Speaker:           | 2 x woofer 5"   |
| Type of speaker:   | Projector speaker   |

|             |                     |
|-------------|---------------------|
| Dimensions: | Depth: 20,5 cm      |
|             | Diameter: Ø 13,8 cm |
| Weight:     | 2,6 kg              |