



Features:

- For switching eight AV sources (audio, composite video and s-video television signals) to up to two television monitors
- 8 inputs (RCA), manually or automatically switchable
- Automatic switching time adjustable from 1 to 25 seconds
- Simultaneous recording to one or two video or DVD recorders
- A HiFi stereo system can be connected via the second output
- For application areas such as: Trade fair and shop fitting; clubs/dancing school; restaurants, bars and hotels

Logistic

EAN / GTIN: 4026397306637
Weight: 1,09 kg
Length: 0.35 m
Width: 0.14 m
Height: 0.06 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	6.00 W
Frequency range:	20 - 100 Hz
S/N ratio:	>100 dB
THD:	<0.05 % at 1 kHz
Dimensions:	Width: 28.2 cm Depth: 12.8 cm Height: 5 cm
Weight:	0.94 kg
Video:	

8 x inputs:	1 Vpp/ 75 ohms, composite RCA
2 x outputs:	1 Vpp/ 75 ohms, composite RCA
Gain:	2 V, 1 V (terminated)/ 75 ohms
Return loss:	>18 dB
Video bandwidth:	>100 MHz
Audio:	
8 x inputs:	22 kohms, stereo RCA
2 x output:	1 kohms, stereo RCA
Gain:	nominal 0 dB
Channel separation:	>75 dB

Scope of delivery: