



The article is no longer in our assortment.

Features:

- More light at a same performance by higher coiled filament temperature
- Longer lifetime by permanent filament renewal (tungsten parts bond to the gaseous halogene parts even before reaching the glass bulb)
- The temperature circulation has the effect that the tungsten parts precipitate again on the filament
- Constant light during lifetime, as no bulb blackening occurs
- Comfortable and fresh, white light
- Dimmable (blackening of the glass bulb in case of dimmed operation is eliminated by a short operating time at full voltage)
- Different illumination angles for different application areas
- Low power consumption
- Long lifetime (Average lifetime 3000 h)
- Special lamp with 50mm reflector
- Reflector with coverglass, therefore UV protection
- High durability
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)

Logistic

EAN / GTIN: 4026397099171

Weight: 0,04 kg

Length: 0.04 m

Width: 0.04 m

Height: 0.06 m

Technical specifications:

Operating voltage: 12 V

Nominal wattage: 20 W

Base: GX5.3

Lamp type:	Halogen lamp; clear lamp; low voltage lamp; sealed beam lamp; halogen bulb; Cool Beam lamp; Self-shielded lamp
Lamp specification:	Dimmable Hot restrike
Beam angle:	12°
Color of light:	White
Color temperature:	2500K
Color rendering index (CRI):	95 Ra
Lead time:	0 s
Construction:	MR-16; Reflector; Bi pin
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	2000 h
Dimensions (LxD):	81x51 mm
Weight:	30 g
Legal specifications	
Energy efficiency class (A++ - E):	D