

OMNILUX MR-11 12V/35W G-4 SP FTE+C

Cool-beam mirrored lamp



The article is no longer in our assortment.

Features:

- More light at a same performance by higher coiled filament temperature
- Longer lifetime by permanent filament renewal (tungsten parts bond to the gaseous halogene parts even before reaching the glass bulb
- The temperature circulation has the effect that the tungsten parts precipitate again on the filament
- Constant light during lifetime, as no bulb blackening occurs
- Comfortable and fresh light
- Dimmable (blackening of the glass bulb in case of dimmed operation is eliminated by a short operating time at full voltage)
- Different illumination angles for different application areas
- Low power consumption
- Special lamp with 30mm reflector
- Reflector with coverglass, therefore UV protection
- Long life
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)

Technical specifications:

| Operating voltage: | 12 V |
|--------------------|------|
| Nominal wattage: | 35 W |
| Base: | G-4 |

Logistic

EAN / GTIN: 4026397101607 Weight: 0,02 kg Length: 0.03 m Width: 0.04 m Heigth: 0.04 m

| Lamp type: | Halogen lamp; clear lamp; low voltage lamp; sealed beam lamp; halogen bulb; Self-shielded lamp; Cool Beam lamp |
|------------------------------------|--|
| Lamp specification: | Dimmable |
| | Hot restrike |
| Beam angle: | 30° |
| Color of light: | White |
| Color temperature: | 2500K |
| Color rendering index (CRI): | 95 Ra |
| Lead time: | 0 s |
| Construction: | Reflector; Bi pin |
| Operating temperature max.: | 40° C |
| Operating temperature min.: | 20° C |
| Burning position: | S180 (universal) |
| Lamp life: | 2000 h |
| Dimensions (LxD): | 35x33 mm |
| Weight: | 20 g |
| Legal specifications | |
| Energy efficiency class (A++ - E): | D |