



L'article n'est plus disponible.

Caractéristiques:

FUTURELIGHT LED PXS-40 Artnet Strip

LED bar for video and pixel mapping applications via Art-Net

- Modular LED strip with 40 pixels for video and pixel mapping applications via Art-Net
- Data and power supply via optional video processor
- Extra bright and colorful projection of videos, animations and graphics
- Modular concept allows the build-up of large areas
- Ideal for rental companies, stage/fair construction and fixed installation
- For use with MADRIX or any other lighting control software supporting Art-Net
- RGB SMD 5050 LEDs, covered by a smooth diffuser plate, provide excellent color rendering and wide viewing angles
- Signal distribution via UTP cable
- Movable mounting bracket for flexible installation
- 40 LED puissantes SMD 5050 3in1 TCL RGB (mélange de couleurs homogène)
- L'appareil est refroidi par refroidissement par convection passive
- Commandé via RDM; ArtNet

FUTURELIGHT PSU-16 Artnet Controller

Video processor for LED PXS-40 + PXS-20 Artnet Strip

- Video processor and power supply unit for LED PXS-40/20 Artnet Strip
- For use with MADRIX or any other lighting control software supporting Art-Net
- Connections for 16 LED PXS-40 Artnet Strips
- 2 x 16-digit LCD screen for menu settings
- Integrated web interface for comfortable configuration and firmware updates through a browser
- Useful software tool scans the network and identifies fixtures

Logistique

- Neutrik PowerCon input and output
- Signal distribution via UTP cable
- Switch-mode power supply for operation between 100 and 240 volts
- Commandé via ArtNet; RDM

Données techniques:

Poids: 33,95 kg

FUTURELIGHT LED PXS-40 Artnet Strip

Puissance totale de raccordement:	18,00 W
Type de protection:	IP20
Type de lampe:	Lampe LED
LED:	40 x SMD 5050 3in1 TCL RGB (mélange de couleurs homogène)
Canaux DMX:	120
Refroidissement:	Refroidissement par convection passive
Commande:	RDM; ArtNet
Couleur du boîtier:	Noir
Dimension:	Longueur : 1 m Profondeur : 3,8 cm Hauteur : 14 cm
Poids:	1,95 kg
Power supply:	28 V DC via video processor (accessory)
Protocol:	Art-Net 3
Pixel configuration:	RGB SMD 5050
Resolution:	40 pixels
Pixel pitch:	25 mm
Brightness:	850 cd/m ² (nits)
Viewing angle:	120°
Display refresh rate:	400 Hz
Video refresh rate:	60 fps
Signal port:	2 x RJ45, CAT5e
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle

FUTURELIGHT PSU-16 Artnet Controller

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	300,00 W
Type de protection:	IP20

Connexion au réseau:	Protocole : ArtNet 3 via 2x RJ-45 (F) version encastrable
Commande:	ArtNet; RDM
Couleur du boîtier:	Noir
Connexions:	Signal via 4 x RJ-45 (F) version encastrable
Dimension:	Largeur : 26 cm Profondeur : 22,6 cm Hauteur : 8 cm
Poids:	2,75 kg