



**L'article n'est plus disponible.**

---

**Caractéristiques:****OMNITRONIC ADI-004M Interface**

USB audio interface with integrated low-noise microphone preamplifiers

- Plug & play audio interface connects microphones, instruments and line signals with your computer for recording and playback
- Compatible with PC and Mac - no setup required
- High-resolution AD/DA converters (16 bits/ 44.1 kHz and 48 kHz) for high-end audio quality
- High-speed USB 2.0 support
- 2 microphone/hi-Z instrument inputs (combination XLR/6.3 mm jack, bal.), switchable
- +48 V phantom power can be switched on, status LED
- Line input (stereo RCA)
- Analog inputs with gain control and signal/clip LED
- Digital S/PDIF input and output (RCA)
- Monitoring of input and output via adjustable stereo headphones output (3.5 mm jack (1/8"))
- Adjustable stereo line output (6.3 mm jack, bal.) for PA applications
- Power supply via USB, supplied 9 V power unit or 9 V block battery
- The interface can also be used without a computer e.g. as an independent microphone preamplifier for direct monitoring
- Incl. USB cable
- Works with any customary software for PC and Mac
- Possibilité de fonctionnement sur batterie/piles

**OMNITRONIC VM-220 S PRO Vocal microphone**

Universal dynamic microphone

- Versatile dynamic microphone with cardioid characteristic

---

**Logistique**

- Ideal for song transmission or instrument controlling
- Well-balanced frequency range for natural sound
- Handles high volumes without distortion
- Effective low frequency proximity effect due to flat top grille
- Low-wear reed switch, silent during operation
- Robust diecast body and solid steel basket, applicable for touring
- Delivery includes XLR/jack cable

## Données techniques:

---

Poids: 1,15 kg

---

### OMNITRONIC ADI-004M Interface

Puissance totale de raccordement: 6,00 W

---

Batterie: 1 x 9,0 V E-Block 6F22 zinc-carbone ci-joint

---

Dimension: Largeur : 14,4 cm  
Profondeur : 12,7 cm  
Hauteur : 5 cm

---

Poids: 650 g

---

Power supply: 9 V AC/DC, 150 mA

---

via USB port, power unit or battery

---

Frequency range: 20-20000 Hz,  $\pm 1$  dB

---

THD: <0.01 %

---

S/N ratio: 90 dB

---

Input impedance: 1 kohms (mic), 40 kohms (hi-Z)

---

Maximum gain: 48 dB

---

Inputs: 2 x hi-Z/mic (combination XLR/6.3 mm jack, bal.),  
1 x line (stereo RCA), S/PDIF (RCA)

---

Outputs: 1 x line L/R (6.3 mm jack, bal.), headphones (3.5 mm stereo jack), S/PDIF (RCA), USB (type B)

---

AD/DA converter: 16 bits

---

Sampler frequency: 44.1 kHz or 48 kHz

---

Required operating system: Windows 98SE/ME/2000/XP/Vista, Mac OS  
9.1/OS X

---

### OMNITRONIC VM-220 S PRO Vocal microphone

Type de micro: Dynamique

---

Plage de fréquence: 100 - 14000 Hz

---

Poids: 500 g

---

Type: Dynamic

---

Directivity pattern: Cardioid

---

Impedance: 600 ohms

---

Sensitivity: -73 dB

---

Connector: 3-pin XLR, bal.

---

Cable:

3-pin XLR, bal./6.3 mm jack, unbal.

---