



L'article n'est plus disponible.

Caractéristiques:

EUROLITE LED PMC-16x20W COB 3200K

PRO COB performance cluster with 4 x 4 matrix

- Equipped with 16 x 20 W COB LED
- 3200 K color temperature
- 3, 16 or 19 DMX channels selectable for various applications
- Each LED can be controlled individually
- Functions: built-in programs and strobe effect with variable speed, dimmer, Master/Slave
- DMX-controlled operation or stand-alone operation with Master/Slave function
- For use on stages, catwalks, crossbeam systems, or decoration
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Locking possibility at the mounting bracket
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- Commandé via stand-alone; DMX; Commande de la musique via Microphone
- Déjà préprogrammé pour %: LED PC-Control 512; Light Captain
- Avec un Angle de départ de 60°

Logistique

ROADINGER Flightcase 2x PMC-16

PRO flightcase for 2 x PMC-16

- Compartments for 2 x PMC-16
- Suitable for 41606200 EUROLITE LED PMC-16x20W COB 3200K and 41606400 EUROLITE LED PMC-16x30W COB RGB

- Interior upholstered with foam
- High-quality workmanship with multiplex birch wood, dark brown laminated
- Aluminum profile frames (25 mm) with rounded edges
- Three-leg, large steel ball corners
- 2 hinges
- 2 high-quality butterfly locks
- 2 case handles
- Matériel de marque
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

Données techniques:

Poids:	24,60 kg
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle

EUROLITE LED PMC-16x20W COB 3200K

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	275 W
Type de protection:	IP20
Type de lampe:	Lampe LED
Température de couleur:	3200K
Fréquence du flash:	1 - 20 Hz
Canaux DMX:	3; 16; 19
Commande:	Stand-alone; DMX; Commande de la musique via Microphone
Préprogrammé dans:	LED PC-Control 512; Light Captain
Angle de départ:	60°
Angle de départ (1/2 pic):	60°
Couleur du boîtier:	Noir
Dimension:	Largeur : 31,5 cm Profondeur : 34,5 cm Hauteur : 34,5 cm
Poids:	8,20 kg
DMX channels:	3/16/19
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	20 Hz
Sound-control:	via built-in microphone
LED number:	16
LED type:	Array 20 W, white
Color temperature:	3200 K
Beam angle:	60°
Dimensions (W x D x H):	345 x 315 x 345 mm

Spécifications juridiques

Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
------------------	--

Utilisation:	Éclairage pour effets de spectacle
--------------	------------------------------------

ROADINGER Flightcase 2x PMC-16

Charge maximale:	50 kg
------------------	-------

Utilisation de la marque:	Matériel de marque
---------------------------	--------------------

Matériau:	Bois multiplex bouleau, 7 mm
-----------	------------------------------

Couleur:	Marron foncé, laminé
----------	----------------------

Dimension:	Largeur : 39 cm Profondeur : 44,5 cm Hauteur : 43 cm
------------	--

Poids:	8,20 kg
--------	---------

Strength:	7 mm
-----------	------

Outside dimensions (W x D x H):	390 x 445 x 430 mm
---------------------------------	--------------------

Inside dimensions (W x D x H):	415 x 355 x 335 mm
--------------------------------	--------------------

Compartment dimensions (W x D x H):	355 x 200 x 335 mm
-------------------------------------	--------------------