

OMNITRONIC EMX-3 4-channel club mixer

PRO 4-channel DJ mixer

Réf. : 10006768

GTIN: 4026397355604



L'article n'est plus disponible.

Caractéristiques:

- 4 channels with gain control, cue button and super-smooth channel faders
- 1 DJ microphone channel with talkover selector and 2-band equalizer
- Pre-fader listening to all stereo input channels and the master output via adjustable stereo headphones output
- Replaceable crossfader for crossfading between input channels with assignment switches
- Master channel with super-smooth fader, 3-band equalizer, mono/stereo selector switch and 10-digit stereo LED level meter
- Adjustable zone output, and record output, independent of the master
- Inputs: 4 x line (stereo RCA), 2 x phono/line (stereo RCA), switchable; 1 x microphone (6.3 mm jack), 1 x microphone (XLR) and headphones (6.3 mm jack)
- Outputs: master (stereo RCA, 6.3 mm jack, bal.), zone and record (both stereo RCA)
- Operation via supplied power unit
- Rack installation, 4 U
- (19") 48,3 cm installation en rack

Logistique

EAN / GTIN: 4026397355604

Poids: 4,55 kg

Longueur: 0.53 m

Largeur: 0.31 m

Hauteur: 0.15 m

Données techniques:

Puissance totale de raccordement:	30,00 W
Plage de fréquence:	20 - 20000 Hz
Conception du boîtier:	(19") 48,3 cm installation en rack
Dimension:	Largeur : 48,3 cm Profondeur : 17,9 cm Hauteur : 8,9 cm

Poids:	3,40 kg
Power supply:	230 V AC, 50 Hz, via supplied power unit
Inputs:	
DJ microphone (front):	3-pin XLR
MIC 2 (rear):	6.3 mm jack (1/4") (bal.)
Impedance:	1 kohms
Minimum input voltage:	1.5 mV RMS
LINE 1-4:	stereo RCA
Impedance:	27 kohms
Minimum input voltage:	150 mV RMS
PHONO 1.2:	stereo RCA
Impedance:	47 kohms
Minimum input voltage:	3 mV RMS
Outputs:	
MASTER:	stereo RCA, 6.3 mm stereo jack (bal.)
ZONE:	stereo RCA
Impedance:	400 ohms
Output voltage:	1 V RMS/ 0 dB
REC:	stereo RCA
Impedance:	5 kohms
Output voltage:	225 mV RMS
Headphones output:	6.3 mm stereo jack (min. 16 ohms)
Tone control (DJ microphone):	
1 x High:	-12 dB to +12 dB/ 10 kHz, ± 1 dB
1 x Low:	-12 dB to +12 dB/ 100 Hz, ± 1 dB
Tone control (MASTER):	
1 x High:	-15 dB to +15 dB/ 40 kHz, ± 1 dB
1 x Middle:	-15 dB to +15 dB/ 40 kHz, ± 1 dB
1 x Low:	-15 dB to +15 dB/ 40 kHz, ± 1 dB
S/N ratio:	>80 dB
Distortion:	0.02%
Dimensions (WxHxD):	483 x 179 x 102 mm (19", 4 U)