

OMNITRONIC RS-802 Recording mixer

Well-structured 8-channel studio and live mixer

Réf. : 10040075

GTIN: 4026397183245



L'article n'est plus disponible.

Caractéristiques:

- Low-noise 8-channel mic/line mixer
- 4 mono inputs with XLR sockets, +48V phantom power and balanced line inputs
- 2 stereo inputs with balanced 6.3 mm jack sockets
- Stereo inputs can also be operated mono
- 3-band EQ for all inputs
- Peak LED per mono input
- Aux Send per channel for controlling external effectors
- Stereo Aux Return with balanced 6.3 mm jack sockets
- Separate Main Mix, Booth and headphones outputs
- Tape inputs assignable to Master, Booth/headphones
- Precise 10-fold stereo LED meter

Logistique

EAN / GTIN: 4026397183245

Poids: 3,25 kg

Longueur: 0.37 m

Largeur: 0.31 m

Hauteur: 0.12 m

Données techniques:

| | |
|-----------------------------------|---|
| Puissance totale de raccordement: | 15,00 W |
| Dimension: | Largeur : 27 cm Profondeur : 25 cm Hauteur : 5,5 cm |
| Poids: | 2,75 kg |
| Power supply: | 2 x 20 V AC, 50/60 Hz via included power unit |
| Inputs: | |

| | |
|-------------------------|-----------------------------|
| 4 x mono | XLR or balanced 6.3 mm jack |
| 2 x stereo | balanced 6.3 mm jacks |
| 1 x Aux Return: | balanced 6.3 mm jacks |
| 1 x Tape In | stereo RCA |
| Outputs: | |
| 1 x Master Out | balanced 6.3 mm jacks |
| 1 x Control Room | balanced 6.3 mm jacks |
| 1 x Aux Send: | balanced 6.3 mm jacks |
| 1 x Tape Out | stereo RCA |
| Frequency range: | |
| Microphone: | 10-60000 Hz, ± 3 dB |
| Mono: | 10-60000 Hz, ± 3 dB |
| Stereo: | 10-55000 Hz, ± 3 dB |
| Distortion: | 0.01 % |
| S/N ratio: | 112 dB |
| Tone control/channel: | |
| Treble: | ± 15 dB at 12 kHz |
| Middle: | ± 15 dB at 2.5 kHz |
| Bass: | ± 15 dB at 80 Hz |
| Dimensions (W x D x H): | 270 x 250 x 55 mm |