


OMNITRONIC RS-2422 Recording mixer

PRO 24-channel studio and live mixer

Réf. : 10040175

GTIN: 4026397243031



L'article n'est plus disponible.

Caractéristiques:

- Low noise 24 channel Mic/Line-mixer
- 16 mono inputs with XLR sockets, +48V Phantom-power and balanced line inputs
- Insert or Direct Out for every mono channel
- 4 stereo inputs with balanced 6.3 mm jack sockets
- Stereo inputs can also be operated mono
- 3-band EQ with semi-parametric mids for all mono inputs
- 4-band EQ for all stereo inputs
- Peak-LED and switchable Low Cut per mono input
- 2 Aux-Send (pre/post) per channel for controlling external effectors and for monitoring
- 2 stereo Aux-Return with balanced 6.3 mm jack sockets
- Separate Main Mix, Control Room and headphones outputs
- Tape inputs and outputs
- Precise 10-LED meter
- 60-mm high-quality faders

Logistique

EAN / GTIN: 4026397243031

Poids: 11,35 kg

Longueur: 0.83 m

Largeur: 0.12 m

Hauteur: 0.43 m

Données techniques:

| | |
|-----------------------------------|---|
| Puissance totale de raccordement: | 25,00 W |
| Dimension: | Largeur : 69 cm Profondeur : 40 cm Hauteur : 5,5 cm |
| Poids: | 10,20 kg |
| Power supply: | 2 x 20 V AC, 50/60 Hz |

via included power unit

Inputs:

| | |
|--------------|-----------------------------|
| 16 mono | XLR or balanced 6.3 mm jack |
| 16 Inserts | 6.3 mm jacks |
| 4 stereo | balanced 6.3 mm jacks |
| 2 Aux-Return | balanced 6.3 mm jacks |
| 1 Tape In | RCA |

Outputs:

| | |
|----------------|-------------------------------|
| 2 Main Out: | XLR and balanced 6.3 mm jacks |
| 1 Control Room | balanced 6.3 mm jacks |
| 2 Aux Send: | balanced 6.3 mm jacks |
| 4 Direct Out | 6.3 mm jacks |
| 1 Tape Out | RCA |
| Headphones | unbalanced 6.3 mm jack |

Frequency range:

| | |
|-------------|-------------------------|
| Microphone: | 10-60000 Hz, ± 3 dB |
| Mono: | 10-60000 Hz, ± 3 dB |
| Stereo: | 10-55000 Hz, ± 3 dB |
| Distortion: | 0.01 % |
| S/N-ratio: | 112 dB |

Tone control/mono channel:

| | |
|-------|-------------------------------|
| High: | ± 15 dB at 12 kHz |
| Mid: | ± 15 dB at 250 Hz - 6 kHz |
| Low: | ± 15 dB at 80 Hz |

Tone control/stereo channel:

| | |
|---------|-----------------------|
| High: | ± 15 dB at 12 kHz |
| Hi Mid: | ± 15 dB at 3 kHz |
| Lo Mid: | ± 15 dB at 500 Hz |
| Bässe: | ± 15 dB at 80 Hz |

| | |
|-------------------------|-------------------|
| Dimensions (W x D x H): | 690 x 400 x 55 mm |
|-------------------------|-------------------|
