

## OMNITRONIC LRS-1002 Live Recording Mixer

Live recording mixer with 10 inputs

Réf. : 10040220

GTIN: 4026397449112



**L'article n'est plus disponible.**

### Caractéristiques:

- 2 mono input channels with gain control, 3-way EQ and pan control
- 2 stereo input channels with 3-way EQ and balance control
- Adjustable stereo aux return input and FX send output
- Inserts for the mono input channels
- Tape input and output
- Separate main mix and control room outputs
- Adjustable headphones output
- +48 V phantom power, can be switched centrally
- Precise 4-digit stereo LED level display
- Operation via supplied power unit

### Logistique

EAN / GTIN: 4026397449112

Poids: 1,85 kg

Longueur: 0.33 m

Largeur: 0.24 m

Hauteur: 0.09 m

### Données techniques:

|                                   |   |
|-----------------------------------|---|
| Puissance totale de raccordement: | 10,00 W   |
| Plage de fréquence:               | 20 - 20000 Hz   |
| Dimension:                        | Largeur : 19 cm<br>Profondeur : 25 cm<br>Hauteur : 5 cm |
| Poids:                            | 1,55 kg   |
| Power supply:                     | 2 x 18.5 V AC, 350 mA<br>via supplied PSU               |

Inputs/sensitivity:

|                 |                                       |
|-----------------|---------------------------------------|
| Mic, mono       | 0.5 mV, combined XLR/6.3 mm jack bal. |
| Insert          | 140 mV, 6.3 mm jack unbal.            |
| Line In, stereo | 60 mV, 6.3 mm jack L/R bal.           |
| Aux Return:     | 60 mV, 6.3 mm jack L/R bal.           |
| Tape In         | 400 mV, RCA L/R                       |

Outputs/level:

|                       |                                  |
|-----------------------|----------------------------------|
| Main Out:             | 800 mV, 6.3 mm jack L/R unbal.   |
| Control Room          | max. 3 V, 6.3 mm jack L/R unbal. |
| FX Send               | max. 10 V, 6.3 mm jack unbal.    |
| Tape Out              | 60 mV, RCA L/R                   |
| Headphones            | 6.3 mm jack unbal.               |
| Headphones impedance: | >8 ohms                          |
| Distortion:           | <0.04 %                          |
| S/N ratio:            | 91 dB                            |

Tone control/channel:

|                         |                   |
|-------------------------|-------------------|
| Treble:                 | ±15 dB at 12 kHz  |
| Middle:                 | ±15 dB at 2.5 kHz |
| Bass:                   | ±15 dB at 80 Hz   |
| Dimensions (W x D x H): | 190 x 250 x 50 mm |