

OMNITRONIC MRS-1402USB Recording Mixer

Compact audio mixer with 14 inputs and USB interface

Réf. : 10040273

GTIN: 4026397513905



Caractéristiques:

- Built-in USB audio interface allows recordings and playback of digital audio files with a computer (PC and Mac)
- Full duplex USB port: simultaneous recording and playback possible
- 4 mono input channels with gain control, 3-way EQ, Low Cut and pan control
- 4 stereo input channels with 3-way EQ, level switch and balance control
- Adjustable stereo aux send output
- Tape input and output
- Separate main mix and control room outputs
- Headphones output
- +48 V phantom power, can be switched centrally
- Precise 4-digit stereo LED level display
- Operation via supplied power unit
- Rugged, compact metal housing

Logistique

EAN / GTIN: 4026397513905

Poids: 2,97 kg

Longueur: 0.43 m

Largeur: 0.30 m

Hauteur: 0.08 m

Données techniques:

Alimentation électrique: 230 V AC, 50 Hz

Puissance totale de raccordement: 28,00 W

Branchement électrique: Alimentation électrique via fiche creuse (M)
version encastrable câble d'alimentation et bloc d'alimentation (inclus dans la livraison)

Tramite

Plage de fréquence: 20 - 20000 Hz

| | |
|-----------------------|---|
| Port USB: | USB 2.0, type B |
| Dimension: | Largeur : 27 cm Profondeur : 21,5 cm Hauteur : 7,2 cm |
| Poids: | 2,72 kg |
| Inputs/sensitivity: | |
| Mic, mono | 0.5 mV, XLR bal. |
| Line In, mono | 1 mV, 6.3 mm jack bal. |
| Line In, stereo | 10 mV, 6.3 mm jack L/R |
| Tape In | 100 mV, RCA L/R |
| Outputs/level: | |
| Main Out: | 650 mV, 6.3 mm jack L/R unbal. |
| Control Room | 2 V max. 6.3 mm jack L/R unbal. |
| Aux Send: | 2 V, 6.3 mm jack unbal. |
| Tape Out | 2 V, RCA L/R |
| Headphones | 2 V, 6.3 mm jack unbal. |
| Distortion: | 0.05 % |
| S/N ratio: | >74 dB |
| Tone control/channel: | |
| Treble: | ±15 dB at 12 kHz |
| Middle: | ±15 dB at 2.5 kHz |
| Bass: | ±15 dB at 80 Hz |
| Phantom power: | +48 V |

Contenu de la livraison:
