

OMNITRONIC LH-070 Active dual DI box XLR

Dual DI box/splitter

Réf. : 10355070

GTIN: 4026397194937



L'article n'est plus disponible.

Caractéristiques:

- Active 2-channel DI box with split mode
- 2 high-impedance XLR signal inputs
- 2 low-impedance XLR outputs
- Switchable to split mode (input 1 routes the signal to both outputs)
- Input sensitivity switchable: +20 dB, 0 dB, -30 dB
- Ground-lift switch eliminates signal interference and ground loop problems
- Phase can be switched
- Hi-cut 10 kHz switchable
- Modern convex housing design with rubber corners for safe positioning
- Stackable
- Cables can be routed under the housing
- Operation with 9 V battery (included)

Logistique

EAN / GTIN: 4026397194937

Poids: 0,75 kg

Longueur: 0.23 m

Largeur: 0.16 m

Hauteur: 0.10 m

Données techniques:

Batterie:	1 x 9,0 V E-Block 6LR61 alcalin au manganèse ci-joint
Plage de fréquence:	10 - 30000 Hz
Dimension:	Largeur : 15 cm Profondeur : 13 cm Hauteur : 6 cm
Poids:	550 g

Power supply:	9 V battery
Current consumption:	approx. 65 mA
Battery life:	6-8 hours
Input impedance:	470 kohms
Output impedance:	600 ohms
Maximum output level:	6 dBu
Dynamic range:	>100 dB
Hi cut:	10 kHz
Input connectors:	2 x XLR, bal.
Output connectors:	2 x XLR, bal.
THD:	0.5 %