

OMNITRONIC LH-075 Tube mic preamplifier

Préamplificateur à tubes 1 canal pour microphone avec limiteur

Réf. : 10355075

GTIN: 4026397194951



Caractéristiques:

- 12AX7 vacuum tube adds warm sound to digital recorders and sound cards
- Signal inputs and outputs via balanced XLR connectors and 6.3 mm jacks
- Limiter can be switched on
- +48 V phantom power can be switched on
- Microphone phase can be switched
- Input attenuation can be switched on (+20 dB)
- Precise 5-digit LED meter with Peak LED for output level
- Adjustable gain
- Adjustable output level
- Modern convex housing design
- Full rubber housing corners for safe operation
- Cables can be routed under the housing
- Operation via supplied power unit

Logistique

EAN / GTIN: 4026397194951

Poids: 1,40 kg

Longueur: 0.23 m

Largeur: 0.16 m

Hauteur: 0.10 m

Données techniques:

Puissance totale de raccordement:	15,00 W
Plage de fréquence:	10 - 20000 Hz
Dimension:	Largeur : 15 cm Profondeur : 6 cm Hauteur : 13 cm
Poids:	1,2 kg

Power supply:	9 V AC, 1500 mA
Input impedance:	2 kohms (XLR), 840 kohms, 6.3 mm jack (1/4")
Output impedance:	600 ohms (XLR), 300 ohms, 6.3 mm jack (1/4")
Maximum output level:	28 dBu (XLR), 22 dBu, 6.3 mm jack (1/4")
Maximum input level:	14 dBu (XLR), 22 dBu, 6.3 mm jack (1/4")
Dynamic range:	>100 dB
Phantom power:	+48 V
Input connectors:	XLR and jack mounting sockets
Output connectors:	XLR and jack mounting plugs
THD:	0.1 %

Contenu de la livraison:
