

OMNITRONIC XO-23SB Active crossover

Répartiteur actif, stéréo 2 canaux et mono 3 canaux

Réf. : 10355631

GTIN: 4026397382907



Caractéristiques:

- 2-way stereo operation
- Additional Subwoofer output switchable from mono to stereo
- 24 dB octave slope
- Crossover frequency control on the front panel
- Frequency range of crossover frequency Low/High band 100 Hz to 7 kHz
- Frequency range of crossover frequency Subwoofer 50 Hz to 350 Hz
- Individual output level controls for all bands
- Low cut switch
- Phase invert control
- XLR inputs and outputs
- Illuminated switches for secure operation in dark environments
- Rack installation

Logistique

EAN / GTIN: 4026397382907

Poids: 2,50 kg

Longueur: 0,56 m

Largeur: 0,20 m

Hauteur: 0,07 m

Données techniques:

Alimentation électrique: 230 V AC, 50 Hz

Puissance totale de raccordement: 10,00 W

Dimension: Largeur : 48,3 cm
Profondeur : 14,7 cm
Hauteur : 4,45 cm

Poids: 2,10 kg

Slope: 24 dB / octave

| | |
|-------------------------|---------------------------|
| Operation modes: | 2-way stereo/mono |
| Input: | Mono/stereo |
| Input impedance: | 10/20 kohms (unb./bal.) |
| Output: | Mono/stereo |
| Output impedance: | 300/150 kohms (unb./bal.) |
| In/out connectors: | XLR |
| S/N ratio: | >100 dB |
| THD: | 0.05% |
| Input gain: | -- to +6 dB |
| Ouptut gain: | -- to +12 dB |
| Low cut: | 30 Hz, -3 dB |
| Phase adjustment: | 0-180° |
| Dimensions (W x D x H): | 483 x 147 x 46 mm |

Contenu de la livraison:
