

OMNITRONIC XO-34 Active crossover

High-quality stereo crossover

Réf. : 10355635

GTIN: 4026397233308



L'article n'est plus disponible.

Caractéristiques:

- 2-way/3-way stereo or 4-way mono operation possible
- 24 dB octave slope
- Crossover frequency control on the front panel
- Frequency range of crossover frequency 450 Hz - 9 kHz switchable to 45 - 900 Hz
- Individual output level controls for all bands
- Individual output mutes for easy band adjustment
- Phase invert control
- Low Cut switch
- XLR in and outputs
- Illuminated switches for secure operation in dark environments
- Rack installation

Logistique

EAN / GTIN: 4026397233308

Poids: 2,70 kg

Longueur: 0.54 m

Largeur: 0.20 m

Hauteur: 0.08 m

Données techniques:

Alimentation électrique: 230 V AC, 50 Hz

Puissance totale de raccordement: 10,00 W

Dimension: Largeur : 48,3 cm
Profondeur : 14,7 cm
Hauteur : 4,45 cm

Poids: 2,25 kg

Slope: 24 dB / octave

Operation modes: 2/3-way stereo or 4-way mono

Input:	Mono/stereo
Input impedance:	10/20 kohms (unb./bal.)
Output:	Mono/stereo
Output impedance:	300/150 kohms (unb./bal.)
In/Out connectors:	XLR
S/N ratio:	>100 dB
Xover frequency range:	45-9000 Hz
THD:	0.05%
Crosstalk:	>80 dB, -3 dB
Input gain:	-- to +6 dB
Output gain:	-- to +12 dB
Low Cut:	30 Hz, -3 dB
Dimensions (W x D x H):	483 x 147 x 46 mm