

## OMNITRONIC SLM-600 SPL Meter

Digital sound level meter with software kit

Réf. : 10360609

GTIN: 4026397467215



**L'article n'est plus disponible.**

### Caractéristiques:

- Digital sound level meter with LCD
- Software kit for data recording and analysis on PCs and laptops
- Supports Windows XP, vista and 7 (32 bit)
- Data transfer via USB port
- Electret condenser microphone cartridge
- Measuring range from 30-130 dB
- Max Hold function
- A and C weighting
- Slow and fast measuring mode
- Additional analog outputs for AC and DC current via 3.5 mm jacks (1/8")
- Operation via 4 x 1.5 V mignon battery (type AA) or USB bus
- Incl. windscreen, batteries, USB cable, software (CD-ROM)
- Possibilité de fonctionnement sur batterie/piles

### Logistique

EAN / GTIN: 4026397467215

Poids: 0,91 kg

Longueur: 0,28 m

Largeur: 0,25 m

Hauteur: 0,07 m

### Données techniques:

Batterie:	4 x 1,5 V AA Mignon LR06 alcaline au manganèse ci-joint
Plage de fréquence:	31,5 - 8500 Hz
Dimension:	Largeur : 14,5 cm Profondeur : 6 cm Hauteur : 11 cm
Poids:	800 g

Power supply:	4 x 1.5 V battery, type AA
	or 5 V DC, 100 mA via USB port
Measuring ranges:	30-80 dB, 40-90 dB, 50-100 dB, 60-110 dB, 70-120 dB, 80-130 dB, 30-130 dB
Accuracy:	±1.5 dB/94 dB, 1kHz
Level weighting:	A or C
Microphone:	electret condenser microphone
AC output:	0.707 V RMS
Output impedance:	600 ohms
DC output:	10 mV
Output impedance:	100 ohms
Supported operating systems:	Windows XP, Vista, 7 (32 bit)