

OMNITRONIC P-3500 Amplifier, 2x1040W/8ohm

Amplificateur de puissance PA extrêmement puissant

Réf. : 10451195

GTIN: 4026397241907



Caractéristiques:

- 2 operating modes can be selected (stereo or bridged)
- 2 x 1040 W/8 ohms
- Enormous power with highest brilliance
- 2 gain controls on the front panel
- All operation modes controllable via LEDs
- LED intensity adjustable via brightness control on the rear panel
- Signal inputs via XLR female or 6.3 mm jack socket
- Input sensitivity adjustable via selector on the rear panel
- Speaker connection via lockable Speaker plugs or Banana/screw combination
- With limiter
- Ground Lift switch against humming
- Bridged switch for bridging
- Many protection circuits for optimized equipment protection
- Very rugged housing
- Rack installation
- High power/weight-relation

Logistique

EAN / GTIN: 4026397241907

Poids: 25,00 kg

Longueur: 0.52 m

Largeur: 0.52 m

Hauteur: 0.18 m

Données techniques:

Alimentation électrique: 115/230 V CA, 50/60 Hz

Puissance totale de raccordement: 4500,00 W

Puissance de sortie: 1040 W RMS (8 Ohm)

Dimension: Largeur : 48,3 cm

Profondeur : 44 cm
Hauteur : 8,9 cm

Poids:	24 kg
Power range:	230 V \pm 10 % (207-253 V)
Power output sine:	
Stereo 8 ohms	2 x 1040 W
8 ohms bridged	1 x 3300 W
Frequency range:	10-50000 Hz, \pm 1.5 dB
Damping factor:	>150
Distortion factor:	0.01 %
Signal-to-noise ratio:	90 dB
Channel separation (at 1 kHz):	70 dB
Min. input sensitivity:	0.77 V/26 dB/1.4 V
Input impedance:	20 kohms (balanced)
Slew rate:	60 V/ μ sec
Input connectors:	2 x XLR female plug, 2 x 6.3 mm jack plug
Output connectors:	2 x Speaker (stereo), 1 x Speaker (bridge), 2 x Banana/screw combination
Control elements:	Power switch, input attenuators (one per channel), Mode switch - Stereo/Parallel/Bridged, Ground Lift, Input-Level-Select (0.77 V/26 dB/1.44 V), limiter
LED indicators (per channel):	Power, Protect, Signal, Mode
Protection circuits:	Short-circuit, DC, Thermal, softstart
Construction:	Steel chassis, aluminum front panel
Minimum mounting depth:	460 mm

Contenu de la livraison:
