

## PSSO HP-3200 Amplifier

High performance amplifier 2 x 1600 W/4 ohms

Réf. : 10451652

GTIN: 4026397308990



## L'article n'est plus disponible.

### Description:

No-frills power packs, housed in modern class-H technology. The HP-series combines high impulse stability and convincing power reserves with moderate weight, coupled with steadfast operational reliability. For this, high quality components and an extensive packet of protective circuits are responsible.

### Logistique

EAN / GTIN: 4026397308990

Poids: 30,70 kg

Longueur: 0.61 m

Largeur: 0.61 m

Hauteur: 0.17 m

### Caractéristiques:

- Class H technology
- Power supply with softstart
- High impulse stability
- Stable metal housing
- Plain design with aluminum front panel
- Rack installation with 2 units
- Complete protection set against overheat, overload, short-circuit, DC, softstart
- 3 operating modes can be selected (stereo, parallel or bridged)
- Electronically balanced inputs via XLR mounting sockets
- Outputs via lockable Speaker plugs
- Operation mode visible via LED display for Signal, Protect and Clip
- Calibrated input controls for exact level control, power switch
- Ground Lift switch against humming
- Bridged switch for bridging
- 30 Hz Low Cut on the rear panel
- Combines superior sound quality with highest reliability at significant lower weight
- Stable permanent power for all models
- Reliable power amp for a wide range of applications

## Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	1520,00 W
Puissance de sortie:	Max. 3200 W 920 W RMS (8 Ohm)
Plage de fréquence:	20 - 20000 Hz
Dimension:	Largeur : 58,3 cm Profondeur : 45,6 cm Hauteur : 8,9 cm
Poids:	28,20 kg
Power output (RMS):	
Stereo 4 ohms	2 x 1600 W
Stereo 8 ohms	2 x 920 W
8 ohms bridged	1 x 3200 W
Signal-to-noise ratio:	>88 dB
Total harmonic distortion:	0.1 %
Damping factor:	450
Voltage gain:	34.3 dB
Slew rate:	30 V/μsec.
Crosstalk:	72 dB
Input sensitivity:	0.77/1/1.4 V
Input impedance:	10/20 kohms (bal./unbal.)
Input connectors:	2 x XLR mounting socket
Output connectors:	2 x Speaker (stereo), 1 x binding post (bridge)
Protection:	Overheat, overload, short-circuit, DC, softstart
Cooling:	2 fans
Controls:	Power switch, input attenuators, mode switch (stereo/parallel/bridged), ground lift
Indicators:	Signal, Clip, Protect, Power
Construction:	Steel chassis, aluminum front panel  Rack installation with 2 U