OMNITRONIC CMP-1200 Dual CD/MP3 player

Double lecteur CD à fonction MP3 pour DJ

Réf. : 10602406

GTIN: 4026397302820

Description:

Sets the tone!
With high quality drives as well as a clearly structured look and precise haptic, Omnitronic's CMP-1200 sets new standard for reasonably priced dual CD players in the entertainment sector. The player convinces with sensitive and colored rubber buttons as well as with easy-turning and accurate jogdials with mode selector. Moreover, the CMP-1200 supports all main features such as anti-shock, instant start, MP3 or automatic beatcounter. A good choice, if you're looking for a fully equipped DJ player at a good price-performance ratio.

Caractéristiques:

- Audio CD/CD-R/CD-RW/MP3 CD
- 2 x 10 seconds anti-shock protection
- 2 alphanumeric LCDs with CD text and ID3 tag indication
- Instant start within 10 ms
- Full CBR/VBR MP3 support
- Easy-turning jog dials with mode selector (fast or frame search) and Pitch Bend function
- Search buttons for fast forward and reverse
- Folder and track search
- Cue function
- Seamless Loop/Reloop function
- Single or continuous play
- Tempo Lock (tonal pitch remains constant)
- Fader start function
- Pitch adjustment ±4 %, ±8 %, ±16 %, ±100 % (MP3 CD ±16 %)
- Pitch adjustment is displayed in %
- Bargraph display

Logistique

EAN / GTIN: 4026397302820
Poids: 8,25 kg
Longueur: 0.54 m
Largeur: 0.45 m
Hauteur: 0.18 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.

- Pitch Bend buttons
- Automatic beat counter (switchable to manual operation)
- Relay function
- Mechanisms are locked in play mode
- Digital outputs, coaxial
- Rack installation, 2 U
- 2 HE

Données techniques:

Alimentation électrique:	115/230 V CA, 50/60 Hz
Puissance totale de raccordement:	26,00 W
Conception du boîtier:	2 HE
Dimension:	Largeur : 48,3 cm Profondeur : 26,5 cm Hauteur : 8,9 cm
Poids:	7,05 kg
Type:	dual CD/MP3 player
Available disc:	CD/-R/-RW in CD-DA and
	MP3 format (8 and 12 cm)
D/A converter:	8-fold/ 1 bit
Sampler frequency:	44.1 kHz
Frame accuracy:	1/75 sec
Pitch adjustment:	±4 %, ±8 %, ±16 %, ±100 % (MP3 CD ±16 %)
Display:	CD text, ID3 tags, elapsed time, remain time, total remain time
Distortion:	0.0052 %
S/N ratio:	120 dB
Frequency range:	20-20000 Hz, ±0.4 dB
Analog audio output:	2 x stereo RCA/ 2 Vrms
Digital audio output:	2 x RCA/ 0.5 V ±0.1 Vpp/ 75 ohms
Dimensions (L x W x H):	482 x 265 x 89 mm (player units),
	482 x 92 x 89 mm (control unit),
	Rack installation with 2 U

Contenu de la livraison:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.