

OMNITRONIC Lecteur mixte CD MP3 CMP-2000

Double lecteur CD à fonction MP3 pour DJ

Réf. : 10602409

GTIN: 4026397478457



Caractéristiques:

- Audio CD, CD-R, CD-RW, MP3 CD
- 2 USB ports for storage media and portable players (FAT 32)
- Easy Source Select: route USB sources to both drives as desired
- Combined Device Access: both drives can access the same USB medium simultaneously
- Access music files more easily and quickly via smart music database management with free PC software Database Builder
- Sort USB devices lightning-fast by title, artist, album and genre
- System menu for user-defined settings
- 2 x 20 seconds anti-shock protection
- Outstanding reading time of the files (instant start within 10 ms)
- Automatic beat counter (switchable to manual operation)
- Master tempo (tonal pitch remains constant when speed is changed)
- 2 alphanumeric LCDs with ID3 tag indication
- Touch-sensitive jog dials with adjustable sensitivity and mode selector: scratch or pitch bend
- Pitch adjustment $\pm 4\%$, $\pm 8\%$, $\pm 16\%$, $\pm 100\%$ (MP3 CD $\pm 16\%$)
- Fader start
- Relay function
- Folder navigation
- Pitch Bend
- Cue/auto cue function
- Seamless loop/reloop
- Single or continuous play
- Repeat function
- Indication of elapsed time, remain time (MP3 files) or total remain time (audio CD)
- Bargraph display
- Pitch adjustment is displayed in %

Logistique

EAN / GTIN: 4026397478457

Poids: 7,90 kg

Longueur: 0.45 m

Largeur: 0.18 m

Hauteur: 0.54 m

- Extra-large play/pause and cue buttons with color illumination
- Drives are locked in play mode
- Rack installation
- The Database Builder software is available in the manufacturer's download section
- Processeur de signal numérique mastertempo
- Samplingrate: 44,1 kHz
- Réglage du niveau: CD-DA $\pm 4\%$, $\pm 8\%$, $\pm 16\%$, $\pm 100\%$
- Réglage du niveau: MP3 $\pm 4\%$, $\pm 8\%$, $\pm 16\%$

Tableau de commande

- (19") 48,3 cm installation en rack 2 HE
- lecteur audio**
- (19") 48,3 cm installation en rack 2 HE

Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	16,00 W
Branchement électrique:	Alimentation électrique via appareils froids (M) version encastrable câble d'alimentation à prise contact de protection (inclus dans la livraison) Tramite
Plage de fréquence:	17 - 20000 Hz
Rapport signal/bruit:	>126 dB
Distorsion harmonique:	<0,008 % avec 1 kHz
DSP:	Processeur de signal numérique mastertempo
Lecteur audio:	Lecteur USB + CD, (ID3 tag), Anti-choc, Seamless loop
Samplingrate:	44,1 kHz
Lecteur de CD-ROM:	Tiroir-lecteur double
Écran:	ID3-Tags , Temps de lecture du titre , Temps de lecture du titre restant , Temps de lecture restant total
Connexions:	Sortie: 2 x RCA stéréo
Format de la musique:	CD, CD-R, CD-RW, CD-DA, MP3
Précision du châssis:	1/75 s
Appareils de stockage appropriés:	Appareils USB max. 32GB (FAT 32)
Réglage du niveau:	CD-DA $\pm 4\%$, $\pm 8\%$, $\pm 16\%$, $\pm 100\%$ MP3 $\pm 4\%$, $\pm 8\%$, $\pm 16\%$
Port USB:	2 x type A
Convertisseur:	8-fach/ 1 bit
Poids:	6,80 kg
Conception du boîtier:	(19") 48,3 cm installation en rack 2 HE
Dimension:	Largeur : 48,3 cm Profondeur : 26,5 cm Hauteur : 8,9 cm
Conception du boîtier:	(19") 48,3 cm installation en rack 2 HE
Dimension:	Largeur : 48,3 cm Profondeur : 9,5 cm Hauteur : 8,9 cm

Contenu de la livraison:

1 x lecteur audio

1 x Tableau de commande