

## OMNITRONIC DD-2520 USB Turntable bk

Direct-drive DJ turntable with switchable phono/line output

Réf. : 10603060  
GTIN: 4026397295009



## L'article n'est plus disponible.

### Description:

Direct-driven record player with phono/line switch

Digitize your old vinyl treasures in a few steps with the direct-driven turntable Omnitronic DD-2520 USB.

Copying is a child's play

Thanks to the integrated USB interface and software you can record your favorite vinyls on your PC. You don't need any drivers, the player is identified automatically. A phono pre-amp is inbuilt and helps you to digitize your music without the need of additional hifi amps or DJ mixers.

Phono/line switch

You can also simply play and enjoy your records with the DD-2520. The switchable phono/line output enables you to connect the player to almost any sound system with phono or line input.

Fully-fledged DJ turntable

As the DD-2520 shows a precision drive, a rugged housing and shock-absorbing feet, it is perfectly suited to as player in your DJ set at home.

### Caractéristiques:

- Built-in USB port and additional phono preamplifier, for a high-quality and convenient digitization of analog vinyl records
- Driver installation not required, unit is identified automatically
- Sampling rates of 44.1 kHz and 48 kHz in stereo, resolution: 16 bits
- Incl. software for recording and editing
- Precision direct drive

### Logistique

EAN / GTIN: 4026397295009

Poids: 12,50 kg

Longueur: 0.53 m

Largeur: 0.41 m

Hauteur: 0.20 m

- Delivery includes pick-up system
  - 2 speeds, pitch control  $\pm 10\%$
  - Large start/stop button
  - Strobe lamp for exact speed adjustment
  - Target lamp
  - Delivery includes removable dustcover
  - Adjustable anti-skating
  - Shock-absorbing feet
  - Switchable output phono/line
  - USB 1.1 support
  - Suitable for Windows XP, Vista, 7 and Mac OS X
  - Réglage du niveau:  $\pm 10\%$
  - L'appareil peut être connecté au PC via USB,
- L'étendue des fournitures**
- 1 x système, 1 x platine

## Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	12,00 W
Branchement électrique:	Fixe Câble d'alimentation à prise euro
Plage de fréquence:	20 - 20000 Hz
Type d'entraînement:	Entraînement direct Moteur à courant continu sans balais
Transmission:	Couple de démarrage : 1 kg/cm Durée de démarrage : 1 sec. Durée de décélération : 1 sec. (transition de la vitesse de rotation : &lt;
Pleurage et scintillement:	<0,15 % WRMS
Grondement:	55 dB DIN B
Vitesse de rotation:	33 tr/min; 45 tr/min
Bras de lecture:	En forme de S avec une suspension à cardan Longueur : 230 Surplomb : 16 mm Force d'appui : 0-4 g, réglable
Niveau de sortie:	Phono 1,5-3,6 mV/ 1 kHz 5 cm/sec Line 90-216 mV/ 1 kHz 5 cm/sec
Connexions:	Sortie: Line/Phono via RCA stéréo Sortie: USB B (F) version encastrable
Réglage du niveau:	$\pm 10\%$
Port USB:	1 x USB 1.1, Typ B
Couleur:	Noir
PC connect:	Via USB
Dimension:	Largeur : 45 cm Profondeur : 35 cm Hauteur : 15,5 cm
Poids:	11,25 kg
Platine	
Dimension:	Diamètre : $\varnothing$ 33 cm