

OMNITRONIC AS-360 Active system

Système actif complet, 360 W RMS

Réf. : 11038802

GTIN: 4026397357493



L'article n'est plus disponible.

Caractéristiques:

- Two-way satellite system consisting of two tops and one subwoofer
- Perfectly tuned system for demanding home users, DJs, musicians, small parties etc.
- Easy-to-use complete system
- Rugged full-range top speaker in a stable wooden housing
- Tops: with passive 2-way crossover
- Sub: powerful, dry bass via optimized double vented bandpass system
- Balanced frequency range with high sound pressure
- Speaker connection via lockable Speaker-plugs
- Scratch-resistant lacquer surface
- Compact speaker system for car transport

Logistique

EAN / GTIN: 4026397357493

Poids: 29,20 kg

Longueur: 0.48 m

Largeur: 0.41 m

Hauteur: 0.64 m

Données techniques:

Alimentation électrique: 230 V AC, 50 Hz

Puissance totale de raccordement: 500,00 W

Puissance de sortie: Max. 360 W

Plage de fréquence: 120 - 20000 Hz

Dimension: Largeur : 35 cm
Profondeur : 14,5 cm
Hauteur : 17 cm

Poids: 26,65 kg

Top:

Rated power:	120 W RMS
Program power:	180 W
Components:	2 x 10 cm woofer (2 x 4"), dome tweeter
Connection:	1 Speaker socket
Sensitivity:	90 dB
Maximum SPL:	108 dB
Impedance:	4 ohms
Dispersion angle:	60° x 60°
Crossover frequency:	3 kHz
Dimensions (H x W x D):	350 x 145 x 170 mm

Subwoofer:

Rated power:	140 W RMS
Program power:	200 W
Components:	20 cm woofer (8")
Sensitivity:	96 dB
Maximum SPL:	114 dB
Impedance:	4 ohms
Dimensions (H x W x D):	430 x 320 x 420 mm

Amplifier:

Total power output:	360 W RMS
Nominal power output satellite:	2 x 120 W RMS
Nominal power output subwoofer:	120 W RMS
Active crossover:	
Crossover frequency:	140 Hz
Inputs:	2 x XLR, 2 x RCA
Outputs:	2 Speaker sockets
Min. input sensitivity:	0.350 V
Control elements:	Power switch, Gain control , Sublevel control
LED indicators (per channel):	Power
Protection circuits:	Short-circuit
