

OMNITRONIC MAXX-1000DSP MK2 2.1 Active System

Powerful active PA (15" sub, 8" tops) with DSP, 1000 watts

Réf. : 11038826

GTIN:



L'article n'est plus disponible.

Caractéristiques:

- Mobile 2.1 system with DSP and 1000 watts RMS power
- Provides perfect sound and good level stability in various kinds of mobile PA applications up to medium-sized party events - ideal for solo entertainers, bands and mobile discos
- 38 cm subwoofer (15") in bassreflex cabinet provides powerful, dry bass
- Two satellites with 20 cm bass-midrange speakers (8") and 3.5 cm driver system (1.4")
- Satellites with passive 2-way crossover, PTC tweeter protection
- Balanced signal input XLR/6.3 mm jack L/R, with level switch
- Additional stereo RCA input
- Parallel XLR line output L/R
- 5 EQ presets with indicators, DSP-controlled
- Signal limiter, DSP-controlled
- Separate volume control for subwoofer and satellites
- Adjustable crossover frequency 80-200 Hz
- Stereo/mono selection
- Subwoofer with plywood enclosure
- Satellites with MDF enclosure
- Enclosure (15 mm) with scratch-resistant lacquer surface, steel grille and flange
- Subwoofer with M20 metal flange for mounting a satellite speaker
- 4 castors, 2 of which with locking brakes
- Delivery includes two speaker cables
- Processeur de signal numérique

Basse

- Roulettes

L'étendue des fournitures

- 1 x basse, 1 x tête d'ampli, 1 x mode d'emploi, 2 x câble d'enceinte, 1 x câble secteur/câble d'alimentation

Logistique

Données techniques:

Puissance totale de raccordement:	280 W Alimentation 1/8
Plage de fréquence:	80 - 19000 Hz Tête d'ampli 45 - 150 Hz Basse
DSP:	Processeur de signal numérique
Commutation:	Class D
Poids:	55,55 kg
Tête d'ampli	
Sensibilité:	95 dB
Pression acoustique max.:	121 dB
Type d'enceinte:	Boîtier compact
Dimension:	Largeur : 26,6 cm Profondeur : 24 cm Hauteur : 41,5 cm
Poids:	10 kg
Basse	
Sensibilité:	97 dB
Pression acoustique max.:	126 dB
Enceinte:	1 x Boumeur 15"
Type d'enceinte:	Subwoofer
Type de construction:	Bassreflex
Aide au transport:	Roulettes
Dimension:	Largeur : 47,6 cm Profondeur : 70 cm Hauteur : 53 cm
Poids:	35 kg
Power supply:	230 V AC, 50 Hz
Amplifier power:	LF 600 W RMS + HF 2 x 200 W RMS
Components:	
Subwoofer:	38 cm woofer (15")
Satellite speakers:	20 cm woofer (8"), 3.6 cm driver (1.4")
Dispersion angle:	50-100° x 55°
Connection:	
Line input:	combination XLR/6.3 mm jack L/R, RCA L/R
Parallel output:	XLR L/R
Satellite:	Speaker L/R
Dimensions (L x W x H):	
Subwoofer:	700 x 476 x 530 mm
Satellite speakers:	240 x 266 x 415 mm
Subwoofer:	35 kg
Satellite speakers:	10 kg

OMNITRONIC MAXX 2.1DSP Satellite 2x

Systeme d'enregistrement:

Ø 35 mm
