

## OMNITRONIC COMPACT-100 1.1 Active system

Mobile and compact active PA system, 100 watts RMS

Réf. : 11038830

GTIN: 4026397512939



### Caractéristiques:

- Mobile column PA system with top speaker and active subwoofer with class D circuitry
- Ultra-compact, extremely light - this system can be installed and setup in no time
- Ideal for DJs, entertainers, small bands and various kinds of mobile PA applications
- Dual class D amplifier (70 W + 30 W RMS)
- 25 cm subwoofer in bassreflex cabinet provides powerful, dry bass
- Top with 16.5 cm bass-midrange speakers and 2.5 cm driver system
- Passive 2-way crossover, PTC tweeter protection
- Balanced XLR/6.3 mm inputs and XLR parallel output
- Master and subwoofer level controls
- Lockable speaker connectors
- Complete protection set against short-circuit, overheat, overload and overcurrent
- Scratch-resistant lacquer surface and flange

### Logistique

EAN / GTIN: 4026397512939

Poids: 31,90 kg

Longueur: 0.56 m

Largeur: 0.42 m

Hauteur: 0.79 m

Article encombrant

### Données techniques:

Alimentation électrique: 115/230 V CA, 50/60 Hz

Puissance totale de raccordement: 150,00 W

Dimension: Largeur : 48,1 cm  
Profondeur : 33,6 cm  
Hauteur : 39,1 cm

Power output sine:

Subwoofer: 70 W RMS

|                         |                                                |
|-------------------------|------------------------------------------------|
| Satellite speakers:     | 30 W RMS                                       |
| Components:             |                                                |
| Subwoofer:              | 25 cm woofer (10")                             |
| Satellite speakers:     | 16.5 cm woofer (6.5"), 2.5 cm tweeter (1")     |
| Frequency range:        |                                                |
| Subwoofer:              | 45-140 Hz                                      |
| Satellite speakers:     | 140-20000 Hz                                   |
| Line input:             | XLR/6.3 mm jack, bal.                          |
| Parallel output:        | XLR                                            |
| Protection circuits:    | Short-circuit, overheat, overload, overcurrent |
| Dimensions (L x W x H): |                                                |
| Subwoofer:              | 81 x 336 x 391 mm                              |
| Satellite speaker:      | 221 x 231 x 359 mm                             |
| Weight:                 |                                                |
| Subwoofer:              | 19 kg                                          |
| Satellite speaker:      | 6.6 kg                                         |

**Contenu de la livraison:**