

OMNITRONIC ASS-1503 Active System

Powerful mobile column PA system, 850 W RMS

Réf. : 11038851

GTIN:



Caractéristiques:

- Mobile column PA system with top speaker and active subwoofer with class D circuitry
- Ultra-compact, extremely light - this system can be installed and setup in no time
- Convinces with excellent speech reproduction and wide coverage
- Ideal for DJs, entertainers, small bands and various kinds of mobile PA applications
- Dual class D amplifier (500 W + 350 W RMS) with SMPS
- 38 cm bassreflex subwoofer
- Fullrange column speaker with 12 x 8 cm drivers
- Balanced 6.3 mm jack input and parallel XLR output
- Master level control with peak indication
- Adjustable crossover frequency for subwoofer
- Phase switchable for subwoofer
- Subwoofer with plywood enclosure
- Column speaker with MDF enclosure
- Scratch-resistant lacquer surface, impact-resistant steel grille and flange
- Delivery includes distance tube, speaker cable and power cable
- Castor set and wheel board available as accessory
- Rouleaux facultatifs

Logistique

Données techniques:

| | |
|-----------------------------------|----------------------|
| Puissance totale de raccordement: | 200 W |
| Enceinte: | 1 x Boumeur 15" |
| Aide au transport: | Rouleaux facultatifs |

| | |
|----------------------|---|
| Poids: | 40,40 kg |
| Power supply: | 115/230 V AC, 50/60 Hz |
| Power output sine: | |
| Subwoofer: | 500 W RMS |
| Satellite speaker: | 350 W RMS |
| Components: | |
| Subwoofer: | 38 cm woofer (15") |
| Satellite speaker: | 12 x 8 cm mid-high driver (12 x 3") |
| Maximum SPL: | |
| Subwoofer: | 122 dB |
| Satellite speaker: | 121 dB |
| Frequency range: | |
| Subwoofer: | 45-180 Hz |
| Satellite speaker: | 120-20000 Hz |
| Crossover frequency: | 40-160 Hz |
| Microphone input: | combination XLR/6.3 mm jack, bal. |
| Line input: | combination XLR/6.3 mm jack, bal. and RCA L/R |
| Speaker output: | 1 x speaker, 4 ohms |

Contenu de la livraison:
