

OMNITRONIC ACS-410BTS Active Column Speaker System

Colonne PA mobile et Bluetooth stéréo, 410 W

Réf. : 11038866

GTIN: 4026397613452



L'article n'est plus disponible.

Description:

The ACS-410BTS is an active column PA system with a high-power subwoofer with 2-channel class D amplifier module and a full-range column speaker for mobile applications. The system offers two mono inputs (XLR and 6.3 mm jack) for microphones and line sources, one stereo input (RCA and 6.3 mm jack), as well as one AUX input for portable audio players. You can stream music wirelessly from your mobile devices via Bluetooth. The amplifier supplies a power of 310 W and 100 W and is protected with a limiter against overload. The column speaker mounts on top of the subwoofer with the included telescope bar. The integrated stereo Bluetooth link allows for wireless stereo operation with 2 systems linked together.

Logistique

EAN / GTIN: 4026397613452

Poids: 19,75 kg

Longueur: 0.65 m

Largeur: 0.49 m

Hauteur: 0.43 m

Caractéristiques:

- Highly portable column PA system with 410 watts power
- Clear, dynamic sound and wide coverage for DJs, musicians, presenters and events
- Stereo Bluetooth link for wireless stereo operation with 2 systems linked together
- 10" bassreflex subwoofer with class D amplifiers (310 W + 100 W)
- Column speaker with 6 x 2" drivers
- Integrated Bluetooth audio streaming
- Built-in 6-channel mixer
- 2 mono inputs mic/line with 2-band EQ and adjustable reverb
- 1 stereo line input
- 1 stereo AUX input connects any non-Bluetooth device
- Volume control per channel
- Adjustable monitor output
- Master level control with limiter indication
- Subwoofer with M20 threaded flange and locking features for secure transport of column speaker and distance tube

- MDF enclosures with scratch-resistant lacquer surface, impact-resistant steel grille and carry handles
- Total weight just 18 kg
- Delivery includes variable distance tube, speaker cable and power cable
- Commandé via Bluetooth

L'étendue des fournitures

- 1 x câble secteur/câble d'alimentation, 1 x câble d'enceinte, 1 x basse, 1 x tête d'ampli, 1 x pied, 1 x mode d'emploi

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	400 W
Branchement électrique:	Alimentation électrique via Appareils froids (M) version encastrable Câble d'alimentation à prise contact de protection (inclus dans la livraison)
Capacité de charge:	Nominale: 100W RMS HF Nominale: 310W RMS LF
Plage de fréquence:	45 - 20000 Hz
Commande:	Bluetooth
Connexions:	Sortie: Enceinte via Boîtier d'enceinte encastrable (F) Sortie: Line via RCA (F) version encastrable Entrée: Line via 1 x RCA stéréo Entrée: Line via 2 x Prise jack 6,3 mm (stéréo) version encastrable Entrée: Mic/Line via 2 x Câble jack XLR/6,35 mm 3 broches (F) prise combo version encastrable Entrée: AUX via 1 x Prise jack 3,5 mm (stéréo) version encastrable
Entrée des canaux:	2 x Stéréo avec Interrupteur Mic-Line via Prise combo (XLR/jack), réglage du canal via Bouton rotatif 1 x Stéréo via Câble jack, réglage du canal via Bouton rotatif 1 x Stéréo via RCA ou câble jack, réglage du canal via Bouton rotatif
Fréquence de rupture:	220 Hz
Enceinte:	1 x Boumeur 10" 6 x Tweeter 2"
Dimension:	Largeur : 33,5 cm Profondeur : 41 cm Hauteur : 57 cm
Poids:	18,10 kg