

## PSSO CLA-228 LINE ARRAY top

Compact line array system

Réf. : 11040900

GTIN: 4026397362688



## L'article n'est plus disponible.

### Description:

Top with defined sound combined with low weight: a mixture which fittingly describes the CLA-228. Suitable for both permanent installations and mobile use. Thanks to the weight, installation is simplified and pressure on the rigging points is relieved. The waveguide was individually developed to produce a coherent sound field. Captive quick lock pins enable an easy installation.

### Logistique

EAN / GTIN: 4026397362688

Poids: 17,40 kg

Longueur: 0.77 m

Largeur: 0.42 m

Hauteur: 0.40 m

### Caractéristiques:

- Compact line array for permanent installations and touring purposes
- Time saving 2-man installation directly from the transport case
- Lightweight housing due to high-quality plastic
- Low weight of the whole construction and reduced demands for the flying points
- Elegant housing design for avoiding resonance and standing waves
- Two powerful 20 cm low/mid neodymium magnets (2 x 8")
- 4.4 cm neodymium driver (1.73") with titanium diaphragm
- Specially designed waveguide
- Maximum efficiency due to biamped control
- Wide horizontal dispersion angle of 100°
- Curving adjustable between 0° and 12°
- Easy rigging with captive quick release pins
- Tight locking pins eliminating vibration noise
- Flying hardware regularly tested by an independent and accredited testing institute
- Neutrik Speakon sockets
- PC software in the manufacturer's download section
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

## Données techniques:

|                         |  |
|-------------------------|--|
| Plage de fréquence:     | 80 - 18000 Hz  |
| Dimension:              | Largeur : 28,5 cm<br>Profondeur : 67 cm<br>Hauteur : 28,5 cm |
| Poids:                  | 14,85 kg   |
| MF rated power:         | 300 W RMS  |
| HF rated power:         | 60 W RMS   |
| MF program power:       | 600 W  |
| HF program power:       | 120 W  |
| Components:             | 2 x 20 cm woofer (2 x 8"), 4.4 cm driver (1.73")             |
| Connection:             | 2 Speakon sockets (4-pin)                                    |
| MF sensitivity:         | 96 dB  |
| HF sensitivity:         | 104 dB   |
| MF maximum SPL:         | 120 dB   |
| HF maximum SPL:         | 121 dB   |
| Impedance:              | MF 16 ohms / HF 16 ohms                                      |
| Crossover frequency:    | 1.3 kHz  |
| Dispersion angle:       | H=100°, V=3°   |
| Dimensions (H x W x D): | 285 x 670 x 285 mm   |