

PSSO K-208 2-Way Top 200W

PRO PA speaker, 8" woofer, 1" horn, 200 W RMS, 8 ohms

Réf. : 11041098

GTIN: 4026397481815



Caractéristiques:

- Rugged full-range top speaker, qualified for suspension and touring applications
- Housing made of 15 mm birch plywood
- 20 cm (8") bass speaker with diecast aluminum basket
- Rotatable 25 mm constant directivity horn tweeter (1", 44 mm voice coil)
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- Passive 2-way crossover
- Bassreflex system
- Parallel Neutrik Speakon connectors
- M10 thread for Omnimount wall brackets
- Adapter for stand installation available as accessory (SPA-10L)
- Trapezoidal multi-functional housing with scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Applications: standing, as monitor, on a subwoofer or speaker stand, suspended
- Pilote de CELTO ACOUSTIQUE
- Connexion enfichable NEUTRIK intégrée
- Développé en europe

Logistique

EAN / GTIN: 4026397481815

Poids: 13,75 kg

Longueur: 0.34 m

Largeur: 0.34 m

Hauteur: 0.52 m

Données techniques:

Capacité de charge: Programme: 400W
Nominale: 200W RMS

Plage de fréquence: 57 - 20000 Hz

Sensibilité: 95 dB

| | |
|---------------------------|---|
| Pression acoustique max.: | 124 dB |
| Dispersion: | 90° x 60° |
| Impédance: | 8 Ohm |
| Connexions: | Entrée: Enceinte via 2 x SpeakON 2 broches version encastrable (F) |
| Fréquence de rupture: | 1800 Hz |
| Enceinte: | 1 x Boumeur 8" 1 x Pavillon 1" |
| Type d'enceinte: | Boîtier compact |
| Utilisation de la marque: | Pilote de CELTO ACOUSTIQUE Connexion enfichable NEUTRIK intégrée |
| Dimension: | Largeur : 27 cm Profondeur : 27 cm Hauteur : 44,5 cm |
| Poids: | 12,50 kg |

Contenu de la livraison:
