

PSSO K-215SE 2-Way Top 600W

PRO PA speaker, 15" woofer, 1.5" horn, 600 W RMS, 8 ohms

Réf. : 11041109

GTIN: 4026397545401



L'article n'est plus disponible.

Caractéristiques:

- Rugged full-range top speaker, qualified for suspension and touring applications
 - Housing made of 15 mm/18 mm birch plywood
 - 38 cm (15") bass speaker with diecast aluminum basket
 - Rotatable constant directivity horn tweeter with titanium diaphragm
 - Horn exit 38 mm (1.5")
 - Voice coil 72 mm (2.8")
 - Premium custom-made drivers by European manufacturer CELTO Acoustique
 - Passive 2-way crossover
 - Bassreflex system
 - Parallel Neutrik Speakon connectors
 - Trapezoidal multi-functional housing with scratch-resistant lacquer surface
 - Impact-resistant steel grille with acoustic foam
 - Dual-angle-Flange for stand installation
 - Applications: standing, as monitor, on a subwoofer or speaker stand, suspended
 - Pilote de CELTO ACOUSTIQUE
 - Connexion enfichable NEUTRIK intégrée
 - Développé en Europe
- L'étendue des fournitures**
- 1 x tête d'ampli, 1 x mode d'emploi

Logistique

EAN / GTIN: 4026397545401

Poids: 32,45 kg

Longueur: 0.51 m

Largeur: 0.49 m

Hauteur: 0.79 m

Article encombrant

Données techniques:

Capacité de charge:

Programme: 1200W

Nominale: 600W RMS

Plage de fréquence:	47 - 19000 Hz
Sensibilité:	99 dB (1 W/1 m)
Pression acoustique max.:	127 dB
Dispersion:	80° x 50°
Impédance:	8 Ohm
Connexions:	Entrée: Enceinte via 2 x SpeakON 2 broches version encastrable (F)
Fréquence de rupture:	1500 Hz
Enceinte:	1 x Boumeur 15" 1 x Pavillon 1,35"
Type d'enceinte:	Boîtier compact
Utilisation de la marque:	Pilote de CELTO ACOUSTIQUE Connexion enfichable NEUTRIK intégrée
Dimension:	Largeur : 44,5 cm Profondeur : 41,5 cm Hauteur : 71 cm
Poids:	29,45 kg