

PSSO K-215X 2-way top 600W

PRO PA speaker system

Réf. : 11041110

GTIN: 4026397483048



L'article n'est plus disponible.

Caractéristiques:

- Rugged full-range top speaker, qualified for suspension and touring applications
- Housing made of 15 mm/18 mm birch plywood
- 38 cm (15") bass speaker with diecast aluminum basket
- Rotatable constant directivity horn tweeter
- Horn exit 35 mm (1.4")
- Voice coil 72 mm (2.8")
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- Passive 2-way crossover
- Bassreflex system
- Parallel Neutrik Speakon connectors
- Trapezoidal multi-functional housing with scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Flange for stand installation
- Applications: standing, as monitor, on a subwoofer or speaker stand, suspended
- Pilote de CELTO ACOUSTIQUE

Logistique

EAN / GTIN: 4026397483048

Poids: 35,00 kg

Longueur: 0.52 m

Largeur: 0.48 m

Hauteur: 0.79 m

Article encombrant

Données techniques:

Capacité de charge: Programme: 1200W
Nominale: 600W RMS

Plage de fréquence: 44 - 19000 Hz

Impédance: 8 Ohm

Connexions:	Entrée: Enceinte via 2 x Boîtier d'enceinte encastrable (F)
Enceinte:	1 x Boumeur 15"
Type d'enceinte:	Boîtier compact
Utilisation de la marque:	Pilote de CELTO ACOUSTIQUE
Dimension:	Largeur : 71 cm Profondeur : 44,5 cm Hauteur : 41,5 cm
Poids:	32,20 kg
Components:	38 cm woofer (15"), 3.6 cm horn (1.4")
Connection:	2 x Speakon
Sensitivity:	98 dB
Maximum SPL:	132 dB
Crossover frequency:	1.5 kHz
Dispersion angle:	80° x 50°
Dimensions (H x W x D):	710 x 445 x 415 mm