



**L'article n'est plus disponible.**

### Caractéristiques:

- Rugged full-range PA top speaker, qualified for suspension and clubs
- Housing made of 18 mm (13 layers) birch plywood
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- 30 cm neodymium bass speaker (12") with diecast aluminum basket
- 36 mm neodymium driver (1.4"), 72 mm voice coil (2.8")
- Passive 2-way crossover
- Bassreflex system
- Parallel Neutrik Speakon connectors
- Movable mounting bracket for ceiling or wall installation
- Scratch-resistant lacquer surface
- Applications: standing, on a subwoofer or suspended
- Pilote de CELTO ACOUSTIQUE
- Développé en Europe

### Logistique

EAN / GTIN: 4026397494013  
Poids: 17,00 kg  
Longueur: 0.48 m  
Largeur: 0.48 m  
Hauteur: 0.49 m

### Données techniques:

Capacité de charge:	Programme: 800W Nominale: 400W RMS
Plage de fréquence:	59 - 21000 Hz
Sensibilité:	100 dB
Pression acoustique max.:	132 dB
Dispersion:	70° x 70°

Impédance:	8 Ohm
Connexions:	Entrée: Enceinte via 2 x SpeakON 4 broches version encastrable (F)
Fréquence de rupture:	1400 Hz
Enceinte:	1 x Boumeur 12" 1 x Pavillon 1,5" Bobine mobile graves 3" Ouverture du raccordement du pavillon 1,35" Pilote de compression à bobine mobile aiguës 3"
Type d'enceinte:	Enceinte coaxiale; Boîtier compact
Utilisation de la marque:	Pilote de CELTO ACOUSTIQUE
Dimension:	Largeur : 38 cm Profondeur : 38 cm Hauteur : 38 cm
Poids:	14,80 kg