


LAVOCE CSF082.00K-4 8" Coaxial Speaker, Ferrite Magnet, Steel Basket Driver : 12603024
200 W AES LF/35 W AES HF, 4 Ohm LF/4 Ohm HF, 96 dB LF/103,5 dB HF, 75-5500 Hz LF/1500-20000 Hz HF GTIN:



Caractéristiques:

- <h2 class="featureSatz">200 W AES LF/35 W AES HF, 4 Ohm LF/4 Ohm HF, 96 dB LF/103,5 dB HF, 75-5500 Hz LF/1500-20000 Hz HF</h2>

Logistique

Données techniques:

Capacité de charge:	Programme: 400W LF Nominale: 200W AES LF Programme: 70W HF Nominale: 35W AES HF
Plage de fréquence:	75 - 5500 Hz LF 1500 - 20000 Hz HF
Sensibilité:	96 dB LF; 103,5 dB HF
Impédance:	4 Ohm LF; 4 Ohm HF
Enceinte:	Boumeur 8" avec shared ferrit magnet with dual demodulating rings Matériau du panier : acier Cônemériau : carton/papier résistant aux intempéries Materiale del cestello Bobine mobile graves 2" Diaphragmematériau : Polyimide Materiale del cestello Pilote de compression aigus 1"

Pilote de compression à bobine mobile aiguës
1,4"

Poids: 3,00 kg

Contenu de la livraison:
