

OMNITRONIC UHF-215 Wireless mic system

UHF multifrequency wireless microphone system

Réf. : 13053505

GTIN: 4026397392142



L'article n'est plus disponible.

Caractéristiques:

- Set includes receiver unit as UHF PLL system and one wireless microphone
- Matches transmitter TM-215 with the same carrier frequency
- Non-Diversity system with one folding antenna
- 16 UHF frequencies (842.000-862.600 MHz) selectable
- LED indicator for power and signal input
- Mic channels switchable via DIP switches
- Output level control
- 6.3 mm and XLR output
- Squelch control to eliminate noise bursts
- Operation via supplied power unit
- Power supply of microphone via 2 x 1.5 V Mignon batteries (type AA) (not supplied)
- Not compatible with 115/315/415 series
- License-free and approved in Germany

Logistique

EAN / GTIN: 4026397392142

Poids: 2,60 kg

Longueur: 0,45 m

Largeur: 0,33 m

Hauteur: 0,10 m

Données techniques:

Alimentation électrique: 230 V AC, 50 Hz

Puissance totale de raccordement: 3,00 W

Bande de fréquences: UHF

Dimension: Largeur : 21 cm
Profondeur : 16,5 cm
Hauteur : 4,4 cm

| | |
|----------------------|--|
| System: | Non diversity, one channel |
| Carrier frequency: | UHF 842.000-862.600 MHz (16 ch) |
| | 842.000 MHz, 842.400 MHz, 844.800 MHz, 846.800 MHz, 850.000 MHz, 854.000 MHz, 859.600 MHz, 845.000 MHz, 845.400 MHz, 847.800 MHz, 849.800 MHz, 853.000 MHz, 857.000 MHz, 862.600 MHz, 855.800 MHz, 856.200 MHz |
| Frequency stability: | ±0.005 % |
| S/N ratio: | >90 dB |
| Input sensitivity: | >80 dB |
| Dynamic range: | >90 dB |
| Modulation method: | FM |
| Frequency range: | 90 Hz - 15 kHz (±3 dB) |
| Audio output: | Mono 6.3 mm jack socket; XLR socket |
| | via 17 V DC, 300 mA power unit included in the delivery |
| Dimensions: | 210 x 165 x 44 mm |
| Weight: | 500 g |
| Microphone: | |
| RF power output: | 10 mW |
| Coverage: | 100 m (with line-of-sight) |
| Battery life: | approx. 6 hours |
| Dimensions (D x H): | 50 x 260 mm |
| Weight: | 360 g |